

(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, ID, TG).

Published:

— with international search report

(48) **Date of publication of this corrected version:**

3 January 2003

(15) Information about Correction:

see PCT Gazette No. 01/2003 of 3 January 2003, Section H

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521

CI OLING SYSTEM FOR A PHOTOCOSMETIC DEVICE .

BACKGROUND OF THE INVENTION

Related Applicati • ns

This appli cation claims priority to provisional application serial number 60/3.63798, filed March 12, 2102. This application is also a continuation-in-part of application serial number 10/052,47 , filed January 18, 2002, which application is a continuation of application serial number 09/4 73,910, filed December 28, 1999, which application claims priority to provisional applic tion serial number 60/115,447, filed January 8, 1999, claims priority from
 10 provisional applic tion serial number 60/164,492, filed November 9, 1999, and is a continuation-in-p. of application serial number 09/078,055, filed May 13, 1998, now U. S. Patent No. 6,273, 84, which application claims priority to provisional application serial number 60/046,5 / , filed May 15, 1997 and provisional application serial number 60/077,726, filed March 12, 1 98. This application is also a continuation-in-part of application serial
 15 nwnber 09/268,43, filed March 12, 1999, which application claims priority to provisional application serial ' umber 60/115,447, filed January 8, 1999 and provisional application serial number 60/077,7' filed January 8, 1999 and is a continuation-in-part of application serial number 08/759,036, filed December 2, 1996, now U. S. Patent No. 6,015,404, and is a continuation-in-put of application serial number 08/759,136, filed December 2, 1996, now
 20 abandoned, and is a continuation-in-part of application serial number 09/078,055, filed May 13, 1998, now U. 3. Patent No. 6,273,884, which application claims priority to provisional application serial ilumber 60/046,542, filed May 15, 1997 and provisional application serial number 60/077,726, filed March 12, 1998. This application is also a continuation-in-part of application serial lumber 09/634,981, filed August 9, 2000, which application is a continuation
 25 of application serif number 09/078,055, filed May 13, 1998, now U. S. Patent No. 6,273,884, which application claims priority to provisional application serial number 60/046,542, filed May 15, 1997 and provisional application serial number 60/077,726, filed March 12, 1998. This application i also a continuation-in-part of application serial number 09/847,043, filed April 30, 2001, w ich claims priority to provisional application serial number 60/200,431, filed
 30 April 28, 2000. s application also claims priority to provisional application serial number 60/292,827, filed ay 23, 2001. This application also claims priority to provisional application serial umber 60/363,871, filed March 12, 2002. The contents of all of these prior application specifications are incorporated herein by reference.

Related Art

There exists a variety of conditions treatable using photocosmetic procedures (also referred to herein as photo cosmetic treatments), including light-based (e.g., using a laser or lamp) hair removal, treatment of various skin lesions, tattoo removal, facial resurfacing, and skin rejuvenation. Currently, photocosmetic procedures are performed using professional-grade devices that cause destructive heating of target structures located in the epidermis/dermis of a patient's skin.

To date, photocosmetic procedures have been performed in a dermatologist's office, partially because of the expense of the devices used to perform the procedures, partially because of safety concerns related to the devices, and partially because of the need to care for optically induced wounds on the patient's skin. Such wounds may arise from damage to a patient's epidermis caused by the highpower radiation and may result in significant pain and/or risk of infection. While certain photocosmetic procedures, such as CO₂ laser facial resurfacing, will continue to be performed in the dermatologist's office for medical reasons (e.g., the need for post-operative wound care), there are a large number of photocosmetic procedures that could be performed in a non-medical environment (e.g., home, barber shop, or spa) if the consumer could perform the procedure in a safe and effective manner. Even for procedures performed in a medical environment, reduced skin damage would reduce recovery time.

Photocosmetic devices for use in medical or non-medical environments may benefit from following characteristics. (1) The device must be safe. For example, it is necessary to avoid eye and skin injuries. (2) Preferably the device is easy to use, thus allowing an operator to achieve acceptable cosmetic results after only reading a brief training period. (3) Preferably the device is robust and rugged enough to withstand abuse. (5) Preferably the device is easy to maintain. (6) Preferably the device is manufacturable in high volume. 7) Preferably the device is available at a reasonable price. (8) Preferably the device is small and easily stored, for example, in a bathroom. Currently available photocosmetic devices have limitations related to one or more of the above challenges.

SUMMARY OF THE INVENTION

A first aspect of the invention is a photocosmetic device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one source of electromagnetic radiation positioned within the treatment head and

- 3 -

configured to project radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, and a mechanism to direct a phase change substance onto the cooling surface. Option ly, the phase change substance comprises a liquid. Alternatively, the phase change substance comprises a solid.

5 In some embodiments of the first aspect, the surface has a texture. The texture may be a linear groove pattern or a concentric groove pattern. Alternatively, the texture is a plurality of projections. The mechanism may be a spray jet. The mechanism may further comprise a valve coupled to the spray jet, wherein the valve controls the amount of liquid projected onto the cooling surface. A heat sensor may be used to produce a signal indicative of the
10 temperature of at least a portion of the area of skin, and a controller may be used to receive the signal from the heat sensor and control the valve in response to the temperature.

A container may be included to hold the substance. In some embodiments, the refrigerant. For example, the refrigerant comprises tetra fluoroethane. The solid may be ice or an organic compound, or an Gallium alloy.

15 The cooling surface may be a thermally conductive electrode providing power to the source. Alternatively, the cooling surface may be a surface of a thermally conductive heat sink that is thermally coupled to the source. The cooling surface may have at least one channel therethrough to receive the phase change substance. Alternatively, the cooling surface has a plurality of channels therethrough to receive the phase change substance, the plurality of
20 channels aligned along the length.

A second aspect of the invention is a photocosmetic device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one electromagnetic radiation source configured to project radiation through the treatment head onto the area of skin, and a first mechanism coupled to the treatment head and configured
25 to project a first substance onto the patient's skin. The electromagnetic radiation source may be positioned with the treatment head. The device may include an optical system to transmit radiation to the area of skin, the optical system having a surface configured to contact the patient's skin. The device may further comprise a cooling surface thermally coupled to the at least one source and said surface; and second mechanism to project a phase change substance
30 onto the cooling surface, wherein the first mechanism is configured to use a gas formed by the phase change of the second substance to drive the first substance onto the patient's skin. The device may further comprising a cooling surface thermally coupled to the source and said

-4-

surface, and a second mechanism configured to project a portion of a first substance onto the cooling surface.

The first substance may be a liquid and the portion of the first substance projected onto the skin is a gas resulting from a phase change of the first substance. Alternatively, the first substance is a solid and the portion of the first substance projected on the skin is a liquid resulting from a phase change of the first substance. In yet another alternative, the first substance is a solid and the portion of the first substance projected onto the skin is a gas resulting from a phase change of the first substance.

The first substance may be a liquid, and the liquid may be a lotion. Alternatively, the first substance may be a gas, and the gas may be cooled air. The second substance may comprise a plurality of components. The cooling surface may be a surface of a thermally conductive electrode providing power to the source. The cooling surface may be a surface of a thermally conductive heat sink that is thermally coupled to the source. Optionally, the source is one of a diode laser bar, light emitting diode and lamp.

A third aspect of the invention is a device for use on an area of patient's skin comprising a treatment head for use in close, proximity to the patient's skin, at least one electromagnetic radiation source positioned in the treatment head and configured to project electromagnetic radiation onto the area of skin, a cooling surface thermally coupled to the at least one source of electromagnetic radiation and including at least one channel therethrough, and a mechanism to project a substance onto the cooling surface, and to the at least one channel.

The substance may be a liquid or a gas.

A fourth aspect of the invention is a device for use on an area of a patient's skin comprising at least one electromagnetic radiation source configured to project radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, and a solid mass thermally coupled to the cooling surface, the solid mass changing phase in response to heat absorbed from the cooling surface.

In some embodiments the solid mass is ice or maybe dry ice. The device may further comprise a mechanism to bring the solid mass into contact with the cooling surface. The device may further comprise a treatment head, wherein the source is positioned within the treatment head. The source may be one of a diode laser bar, light emitting diode and lamp.

The cooling surface is a surface of a thermally conductive electrode providing power to the source or a thermally conductive heat sink that is thermally coupled to the source.

-5-

A fifth aspect of the invention is a device for use on an area of a patient's skin comprising at least one electromagnetic radiation source configured to project electromagnetic radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, a solid mass thermally coupled to the cooling surface, at least a portion of the mass becoming a liquid in response to absorption of heat from the cooling surface, and an exhaust vent configured to receive a portion of the liquid and project the portion of the liquid onto the patient's skin.

The device may further comprise a mechanism for combining the liquid with a chemical substance and projecting the liquid and chemical combination onto the patient's skin.

A sixth aspect of the invention is a device for use on an area of a patient's skin comprising at least one electromagnetic radiation source configured to project electromagnetic radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, and a reaction chamber thermally coupled to the cooling surface and containing at least a first chemical compound and a second chemical compound, the first and second chemical compounds reacting to provide an endothermic reaction within the reaction chamber.

The cooling surface may be a surface of a thermally conductive electrode providing power to the source, or the cooling surface may be a surface of a thermally conductive heat sink that is thermally coupled to the source.

A seventh aspect of the invention is a device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one source of electromagnetic radiation positioned in the treatment head and configured to project electromagnetic radiation onto the area of skin, and a cooling surface thermally coupled to the at least one source of electromagnetic radiation, the cooling surface having a channel therethrough to allow a low-boiling point liquid to flow onto a surface of the cooling surface.

The device may further comprise a valve connected to the channel to control the evaporation of the low-boiling point liquid. The device may also further comprise a heat sensor to produce a signal indicative of the temperature of the area of skin, and a controller to receive the signal from the heat sensor and control the valve in response to the signal. The device may have a pressure source coupled to the channel to control the boiling of the low-boiling point liquid. The source is one of a laser diode bar, light emitting diode and lamp.

The eighth aspect of the invention is a device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one

-6-

electromagnetic radiation source positioned in the treatment head and configured to project radiation onto the area of skin, a heat spreader thermally coupled to at least one source, and a cooling surface, thermally coupled to the heat spreader. The source may be one of a diode laser bar, light emitting diode and lamp. The cooling surface may be surface of a thermally conductive electrode providing power to the source, or may be a surface of a thermally conductive heat sink that is thermally coupled to the source.

A ninth aspect of the invention is a cooling system for cooling heat generating device a cooling surface thermally coupled to the heat generating device, and a nozzle configured to project a high pressure liquid, the liquid forming a flowing liquid on the cooling surface. The high pressure liquid may be projected such that the liquid forms a stream of liquid the entire distance between the nozzle and the cooling surface. The cooling surface may be textured. Optionally the cooling system may further comprise a cooling chamber to redirect the liquid to the cooling surface. The cooling chamber may include sidewalls and a cover. While many of the embodiments are described with reference to performing photocosmetic treatments in a non-medical environment, it is to be understood that the benefits of aspects of this invention apply to medical devices as well as non-medical devices, and the invention applies to either without limitation.

BRIEF DESCRIPTION OF THE DRAWINGS

Illustrative, non-limiting embodiments of the present invention will be described by way of example with reference to the accompanying drawings, in which the same reference numeral is for the common elements in the various figures, and in which

FIG. 1 is a schematic illustration of some basic elements of a photocosmetic device according to some aspects of the present invention;

FIG. 2A is a side view of one example of a radiation system according to some aspects of the present invention for use in performing a photocosmetic procedure on an area of a patient's skin;

FIG. 2B is a schematic top view of an irradiated area of a patient's skin taken along lines 2B — 2B' of FIG. 2A;

FIG. 3 is a side view of an example of a radiation system that is capable of forming two areas of radiation on an area of a patient's skin;

FIG. 4 is a top view of one example of a system appropriate for formation of islands of treatment;

FIG. 5 is a schematic cross-sectional side view of one embodiment of a head according to aspects of the present invention;

FIG. 6A is a cross-sectional side view one example of one embodiment of a cooling system that uses vaporative cooling;

5 FIG. 6B is a cross-sectional side view of another embodiment of a cooling system utilizing a cooling liquid;

FIG. 6C is a schematic of another embodiment of a cooling system utilizing a cooling liquid and having a cooling chamber;

10 FIG. 6D is a cross-sectional side view of an embodiment of a head utilizing a cooling liquid in which the exhaust vent is separated from the port through which cooling liquid enters the chamber;

FIG. 7 is a cross-sectional side view of an embodiment of a cooling system having channels;

15 FIG. 8 is a cross-sectional side view of another embodiment of a head utilizing vaporative cooling of a liquid;

FIG. 9 is a cross-sectional side view of an embodiment of a cooling system using a solid phase-change material according to aspects of the present invention;

FIG. 10 is a cross-sectional side view of an embodiment of a cooling system using an endothermic chemical reaction for cooling;

20 FIG. 11 is a cross-sectional side view of an embodiment of a device having an exhaust vent to cool a patient's skin;

FIG. 12A is a side view of one example of an embodiment of a single-element optical system appropriate for use with photocosmetic devices according to some aspects of the present invention;

25 FIG. 12B is a ray trace of one example of an embodiment of an optical system as illustrated in FIG. 12A;

FIG. 13A is a side view of one example of an embodiment of a two-element cylindrical optical system appropriate for use with photocosmetic devices according to some aspects of the present invention;

30 FIG. 13B is a ray trace of one example of an embodiment of an optical system as illustrated in FIG. 13A;

FICA. 14A is a side view of another example of a embodiment f a two-element cylindrical optical system appropriate for use with photo cosmetic dev:i ces according to some aspects of the present invention;

FIG. 14B is a ray trace of one example of an embodiment of .. optical system as
5 illustrated in FIG. 14A;

FIG. 15A is a side view of another example of a embodiment f a two-element cylindrical optical system appropriate for use with photocosmetic dev ces according to some aspects of the present invention;

FIG. 15B is a ray trace of one example of an embodiment of .. optical system as
10 illustrated in FIG. 15 A;

FIG. 16A is a schematic illustration of an exemplary embod* ent of a head for performing photocosmetic procedures;

FIG. 16B is a schematic illustration of an exemplary embodi~~ment~~ performing photocosmetic procedures that also provides the capabili ' to perform muscle
15 stimulation during a photocosmetic procedure;

FIG. 17A is a schematic of one example of one embodiment o f an apparatus according to some aspects of the invention, which optically determines contact ~~between an optical~~ element and the surface of a patient's skin;

FIG. 17B is a schematic of one example of one embodiment o f an apparatus according
20 to some aspects of the invention, which optically determines contact ~~between an optical~~ element and the surface of a patient's skin;

FIG. 17C is a schematic of one example of one embodiment o an apparatus according to some aspects of the invention, which electrically determines contac ~~t between an optical~~ element and the surface of a patient's skin;

FIG. 18A is a cutaway side view of one embodiment of a han d~~piece~~ having a motion
25 sensor;

FIG. 18B is a schematic of one example of an embodiment of motion sensor system;

FIG. 19 is a schematic of another example of an apparatus ha . g an optical motion
sensor;

FIG. 20 is a schematic of one example of one embodiment of . handpiece illustrating
30 some aspects of a self-contained photocosmetic device according to . e present invention;

FIG. 21 is a schematic of one example of an embodiment of a . andpiece docking station for docking a self-contained photocosmetic device;

-9-

FIG. 22 is a schematic of one example of one embodiment of a handpiece having a detachable head;

FIG. 23 is a schematic illustrating a modular handpiece having one or more components suitable for user-replacement;

5 FIG. 24 is a schematic illustrating a modular optical assembly having one or more components suitable for user-replacement;

FIG. 25 is a schematic of one example of a photocosmetic device illustrating some aspects of the present invention;

10 FIG. 26A is a schematic of one example of a photocosmetic head illustrating aspects of the present invention directed to treating a curved area of skin;

FIG. 26B is a schematic of one embodiment of two transmission systems of a head to treat a curved surface;

FIG. 27 is schematic illustrating an embodiment of some aspects of handpiece 2700 according to the present invention; and

15 FIG. 28 is schematic illustration of one embodiment of a photocosmetic device according to at least some aspects of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

20 FIG. 1 is a schematic illustration of some basic elements of a photocosmetic device 100 according to some aspects of the present invention. Area 110 is an area of a patient's skin on which a selected photocosmetic treatment is to be performed. Area of skin 110 has a basal layer 140 in between an epidermal layer 120 and a dermal layer 130. Typically, photocosmetic treatments involve treating a target area located within epidermal layer 120 or dermal layer 130. For example, in the case of hair removal, it may be desirable to heat a bulb 150 of a hair follicle 160. Alternatively, only a portion of bulb 150 may be heated, for example, the basement membrane 152 between the papilla and the follicle.

In some embodiments of the present invention, the major sub-systems of device 100 include a handpiece 170, a base unit 120 and cord 126 to couple handpiece 170 to base unit 120. Base unit 120 may include a power supply 124 to power control electronics 122 and an electromagnetic radiation (EMR) source 125. Power supply 124 can be coupled to handpiece 170 via cord 126. Cord 126 is preferably lightweight and flexible. Alternatively, as described with reference to FIG. 21 below, cord 126 may be omitted and base unit 120 may be used as a charging station for a rechargeable power source (e.g., batteries or capacitors) located in

-10-

handpiece 170. In some embodiments, base unit 120 can be completely eliminated by including a rechargeable power source and an AC adapter in the handpiece 170.

Handpiece 170 includes a treatment head 180 (also referred to simply as a head) configured to be in contact with a patient's skin, and a handle 190 that may be grasped by an operator to move head 180 in any direction across the patient's skin. For example, head 180 may be pushed across the skin in a forward direction 105 or pulled across the skin in a backward direction 106. Typically, during a given stroke, contact will be maintained between head 180 and the patient's skin 110 while head 180 is moved. Handpiece 170 may be mechanically driven or hand-scanned across the skin surface of area 110. Firm contact between head 180 and skin 110 is preferable to ensure, good thermal and optical contact. As described in greater detail below, in some embodiments of the present invention, head 180 and/or area of skin 110 are cooled by a passive or active cooling apparatus to prevent damage to the head and reduce the occurrence of skin damage (e.g., wounds).

In an exemplary embodiment, source 125 is located in handpiece 170, for example in head 180. Alternatively, source 125 is located in base unit 120 and connected to head 180 via an optical fiber 128. Optical fiber 128 may extend through handle 190, or may be otherwise connected to head 180 for the purpose of delivering light to the patient.

In some embodiments, controls 122 receive information from head 180 over lines 132, for example information relating to contact of head 180 with skin 110, the rate of movement of head 180 over the patient's skin, and/or skin temperature. Controls 122 may transmit control signals to head 180 over lines 132. Lines 132 may be part of a cable that is also connected to head 180 through handle 190 or may be otherwise connected to the head. Controls 122 may also generate outputs to control the operation of source 125 and may so receive information from the source. Controls 122 may also control a selected output device 119, for example an audio output device (e.g., buzzer), optical output device, a sensory output device (e.g., vibrator), or other feedback control to an operator. Depending on operator preference, other commonly used output devices may also be used. In some embodiments, output device 119 is located within handpiece 170.

FIG. 2A is a side view of one example of an illumination system 200 according to some aspects of the present invention for use in performing a photocosmetic procedure on an area of a patient's skin 110. FIG. 2B is a schematic top view of an irradiated area of a patient's skin 110 taken along lines 2B — 2B' of FIG. 2A. In an exemplary embodiment of the invention,

- 11 -

system 20a, including an EMR source 204, is located in the head of a photocosmetic device (e.g., head 180 FIG. 1) such that the EMR source is located proximate the skin surface 110.

Depending on the treatment to be performed, source 204 may be configured to emit at a single wavelength, multiple wavelengths, or in a wavelength band. Source 204 may be a coherent light source, for example a ruby, alexandrite or other solid state laser, gas laser, diode laser bar, or other suitable laser light source. Alternatively source 204 may be an incoherent light source for example, an LED, arc lamp, flashlamp, fluorescent lamp, halogen lamp, halide lamp or other suitable lamp.

An optical system 206, comprised of a plurality of optical elements, includes a surface 207 for transmitting radiation from an EMR source 204 and for contacting the patient's skin 110. Further details of optical system 206, are given below with reference to FIG. 12 - 16. The phrase "optical system" is used herein to refer to a system for transmitting any type of optical radiation suitable for performing photocosmetic procedures.

In some embodiments, source 204 has an extended dimension in the x-direction (e.g., the light source is substantially linear). One of ordinary skill would understand that a plurality of point sources may be combined to form a substantially linear source. Additionally, several sources may be combined to form a single, longer continuous linear source, or a longer linear source having one or more discontinuities. For example, source 204 may be a diode laser bar having a 1 cm long emission line and a few micron line width; alternatively source 204 may include two or three bars placed in a line along the x-direction to create a 2 cm or 3 cm long emission line.

Alternatively, linear sources may be placed adjacent to one another in the y-direction to form a source having an increased line width. System 200 may include one or more additional sources 205, similarly or differently configured than the one or more sources 204. In embodiments having two sources, source 204 and source 205 may emit at the same or different ranges.

In embodiments having multiple EMR sources 204, 205, it may be desirable to activate only selected sources for a given treatment. For example, in embodiments having sources emitting at different wavelengths, for certain applications, for example, hair removal, it may be preferable to only activate a selected one or more sources and for certain other applications, for example, acne treatment or skin rejuvenation, to activate a selected one or more sources. While sources are discussed as emitting radiation at a wavelength, one of

-12-

ordinary skill would understand that any radiation source produces light at a range of wavelengths, accordingly a specified wavelength may be a part of a broader range.

Radiation source 204 may be a pulsed or continuous wave (CW) source. For applications that require coverage of large areas such as hair removal, CW diode laser bars may be preferable. A method of utilizing continuous wave (CW) light sources for the treatment of various dermatologic disorders is described in U. S. Patent No. 6,238,84 B1 entitled "Methods and Apparatus for Dermatology Treatment," to Altshuler, et al., the substance of which is hereby incorporated by reference. Some aspects of that patent teach the use of a CW light source in combination with a contact optical delivery system that can be either hand-scanned or mechanically driven across the skin surface to create a precise temperature rise in the targeted biological structures (i.e., using continuous contact scanning (CCS)).

Most commercial diode laser bars exhibit lifetimes of >5000 hours, but application according to the present invention may only require 10-100 hour lifetimes. Accordingly, in some embodiments of the present invention, a source 204 may be overdriven with current to increase radiation output, thus causing the diode laser to operate at a higher temperature, and thereby sacrificing lifetime.

Diode laser bars appropriate for use with the present invention include diode laser bars emitting at wavelengths of 790-980 nm or other suitable wavelengths. Examples of sources of diode laser bars appropriate for use with aspects of the present invention include Coherent inc. of Santa Clara, CA, or Spectra Physics of Mountain View, CA. The above examples of sources 204, 205 are exemplary and it should be understood that aspects of the present invention include devices and apparatus using any appropriate EMR source currently available or yet-to-be-developed.

For some embodiments of the present invention, for example, those requiring either low power or for treatment of small areas of a patient's skin, LEDs may be used as light sources. Similar to the diode laser sources discussed above, multiple LEDs emitting at different wavelengths could be used in a single optical system. Typical lifetimes for LEDs are in the 50,000-hour range; similar to laser diodes, it may be possible to overdrive an LED and sacrifice lifetime to generate higher optical power. For applications that require high power density, a reflective concentrator (e.g., a parabolic reflector) could be used to decrease the spot size at the skin surface.

Broadband sources (e.g., low-power halogen lamps, arc lamps and halide lamps) are another type of light source that could be used as sources 204, 205. One or more optical filters

-13-

240 and 242 can be used to provide a wavelength band of interest for a given application. Multiple lamps can be combined to produce high power, and, similar to the case of LEDs, a concentrator could be used to decrease the spot size at the skin surface. In some embodiments, several different types of light sources can be incorporated into a photocosmetic device (e.g., device 100 of FIG. 1).

In some embodiments of system 200, a beam splitter 230 splits radiation from source 204 to form a first portion of EMR and a second portion of EMR. The first portion and second portion may be filtered by filters 240 and 242 respectively. After filtering, the portions may have the same or different wavelength ranges. The functions of the first and second portions may be the same or different. For example, the function of the second portion of EMR may be to preheat the patient's skin 110 in preparation for treatment by the first portion of EMR. Alternatively, both the first portion of EMR and the second portion of EMR may provide treatment.

Referring to FIG. 2B, in some embodiments, optical system 206 (visible in FIG. 2A) is configured to form a first area of radiation 210 along a first axis 211 on the patient's skin 110. First area of radiation 210 is formed from at least a first portion of electromagnetic radiation from source 204 (visible in FIG. 2A). In some embodiments, a second area of radiation 220 along a second axis 221 is formed on the patient's skin 110. Second area of radiation 220 may be formed from a second portion of electromagnetic radiation from the radiation source 204; alternatively, a second area of radiation 220 may be formed from light from a second radiation source 205 (visible in FIG. 2A).

In some aspects of the present invention, the first axis 211 and second axes 221 are parallel; however, in other embodiments, the axes 211, 221 are not parallel. System 206 may be configured to form the first area 210 at a selected distance from the second area 220, or may be configured such that the first portion of radiation overlaps at least a part of the second portion of radiation. Optionally, system 206 is configured to form (e.g., focus or collimate) the first portion and second portion substantially as lines. Optical system 200 may be configured to produce one or more lines of light at the skin surface, each having a length of 1-300 mm and a width of 0.1-1 mm. Astigmatism of the beam can be in the range 0.01-0.5. The term "astigmatism" is herein defined to mean the ratio of beam width to the beam length. Also, optionally, system 206 may be configured to form one or more additional areas of radiation along additional axes (not shown) on the patient's skin 110, the additional areas of radiation

- 14 -

formed from corresponding additional portions of electromagnetic radiation from the radiation source 204 or 205, or radiation from one or more additional radiation sources.

FIG. 3 is a side view of another example of an illumination system 300 for use in performing photocosmetic procedures, that is capable of forming two areas of radiation 311, 316 on an area of a patient's skin 110. In system 300, two optical systems 310, 315, instead of a single optical system 206 (Fig. 2), each generate a corresponding area of radiation 311, 316 (e.g., areas of radiation 210, 220). The radiation used to generate the areas may be from two sources 304, 305 or a single divided source as described above with reference to FIG. 2.

FIG. 4 is a top view of one example of an illumination system 400 appropriate for formation of islands of treatment. System 400 includes a plurality of sources 410 (e.g., a conventional laser diode emitting a line or circular spot of illumination), each having a corresponding optical system 415 to direct light onto an area of skin. The illustrated system may be used to create a square (or arbitrarily shaped) matrix of focal spots having islands of treatment within the area of skin. The term "island" as used here is defined to mean an area of specified treatment separated from other areas of the specified treatment, such that areas between two or more areas receive radiation in an amount below that necessary to, achieve the specified treatment. Islands of illumination are discussed in greater detail in U.S. Provisional Patent Application 10/033,302, filed December 27, 2001, by Anderson, entitled "Method and Apparatus for EMR Treatment" the substance of which is hereby incorporated by reference.

For embodiments of photocosmetic devices according to the present invention that utilize high-power sources, management of waste heat from the sources is important for avoiding wounds and other injuries to the consumer. For example, in the case of a photocosmetic device that includes diode laser bars in the handpiece, up to 60% of the electrical energy may be dissipated in non-optical waste heat. In addition to the removal of heat to avoid wounds, removal of heat may be important to prevent the source from overheating and shortening the lifetime of the source.

FIG. 5 is a schematic cross-sectional side view of one embodiment of a head 500 according to aspects of the present invention. Head 500 includes an illumination system including an EMR source (e.g., diode laser bar 510) and an optical system 520. Head 500 may be located in a housing to protect the optical components and to protect the operator of a photocosmetic device; the housing is omitted to avoid obfuscation. In FIG. 5, a diode laser bar 510 operates as the source of electromagnetic radiation (e.g., source 204 in FIG. 2) and may be used to form one or more areas of radiation (e.g., 210, 220 in FIG. 2). Diode laser bar 510 is

-15-

located between positive electrode 515 and negative electrode 516. Electrodes 515, 516 provide electrical power to diode laser bar 510, and may be made of any suitable material having good electrical conductivity. In some embodiments, electrodes 515, 516 are in thermal contact with diode laser bar 510, and have good thermal conductivity to transfer waste heat away from diode laser bar 510. For example, electrodes 515 and 516 may be made of aluminum or copper.

Optionally, waste heat from diode laser bar 510 may be transferred via electrodes 515 and 516 to a heat sink 530. Heat sink 530 may be made of any material having good thermal conductivity to transfer waste heat away from diode bar 510. For example, heat sink 530 may be made of aluminum or copper. Heat sink 530 can be cooled by any appropriate, known method of cooling including a stream of air. Optionally, cooling may be enhanced by adding fins (not shown) to heat sink 530. Alternatively, heat sink 530 may be cooled by one or more of the heat removal methods discussed below with reference to FIGS. 6-11. Also optionally, a heat spreader 522 may be located between electrodes 515, 516 and heat sink 530. Heat spreader 522 is thermally coupled to electrodes 515, 516 and heat sink 530. Heat spreader 522 may be made of any suitable material having good thermal conductivity; preferably heat spreader 522 is electrically insulative. Diamond and carbon fiber are two examples of materials suitable for use as heat spreaders.

In some embodiments, electrodes 515, 516 are configured to be heat sinks to conduct waste heat away from diode laser bar 510. Accordingly, heat sink 530 and heat spreader 522 may be omitted. In such embodiments, electrodes 515 and 516 can be made of any material exhibiting good thermal and electrical conductivity. Optionally, one or more thermal sensors 524 (e.g. a thermocouple, a thermistor) may be used to monitor a temperature indicative of a patient's skin. (e.g., the temperature at the interface of an optical system 520 and electrode 516) for use in a cooling system as described below.

Diode laser bar 510 may be secured to electrodes 515 and 516 using any method capable of maintaining good electrical contact between bar 510 and electrodes 515, 516. In embodiments where transfer of waste heat is desired, any suitable method of achieving good thermal and electrical contact may be used. In one embodiment, diode laser bar 510 is clamped between the two electrodes 515 and 516. A spring or other suitable device may be used to clamp diode laser bar 510 firmly between electrodes 515, 516. In another embodiment, diode laser bar 510 may also be glued in place with thermally/electrically conductive epoxy. In another embodiment, diode laser bar 510 is soldered in place with a low-temperature solder (In

- 16 -

or Au/Sn ;older, etc.). Automated soldering may be achieved using indium preform placed between diode laser bar 510 and electrodes 515 and 516, and applying heat using a die bonder to heat, compress, and then cool the solder and diode bar. Optionally a spacer 525, made out of a material with high thermal and low electrical conductivity such as BeO, may be included to provide electrical insulation between the electrodes 515 and 516.

According to some aspects of the present invention, optical system 520 couples light from diode laser bar 510 to a patient's skin. Optical system 520 may be separated from diode laser bar 510 by an air gap 511. Exemplary optical systems 520 are described in greater detail below with reference to FIGs. 12 - 15. In embodiments according to some aspects of the present invention, optical system 520 is configured to contact an area of a patient's skin, and the optical surface 521 is cooled to provide cooling to the patient's skin.

In some embodiments, cooling of diode laser bar 510 and optical system 520 are achieved using a single cooling system. For example, electrodes 515, 516 may be thermally coupled to optical system 520 along dimensions A; accordingly, both diode laser bar 510 and optical system 520 may be cooled by cooling the electrodes 515, 516 directly or via cooling of a heat sink 530 that is thermally coupled to electrodes 515, 516. Dimensions A are typically both between roughly 1 and 10 mm. Further detail regarding simultaneous cooling of an optical source and an optical system are given in U.S. application serial number 09/473,910, filed December 28, 1999, the substance of which is hereby incorporated by reference.

Contact cooling of the skin may be used to protect a patient's epidermis during delivery of high-fluence radiation to the skin, for example at wavelengths where melanin exhibits significant absorption. In some embodiments of head 500, optical system 520 includes a sapphire element configured to contact a patient's skin due to its good optical transmissivity and thermal conductivity. As described above, optical system 520 may be cooled to remove heat from the sapphire element during treatment. Optionally, prior to treatment with the photocosmetic device, a lotion that is transparent at the operative wavelength(s) may be applied on the skin. Preferably, the lotion is thermally conductive to enhance heat removal from the skin through optical surface 521. Preferably, the lotion also facilitates the gliding motion of the optical system 520 over the skin surface and has a refractive index match between contact surface 520 and the skin 110 to provide efficient optical coupling of the radiation into the skin.

The lotion may also be used to show which skin areas have been treated by choosing a lotion with optical properties (e.g., color or reflectance) that are altered in response to

- 17 -

irradiation bran' MR source (e.g., laser diode 510). For example, if the lotion is initially a given color, after irradiation it would become transparent (or a different color). The ability to distinguish treated from untreated areas is particularly important for treatments such as hair removal that are performed over a large surface area.

FIG. 5 also illustrates one embodiment of a system for cooling diode bar 510 and optical system 52 via heat sink 530. In FIG. 5, a heat absorptive liquid flows through a thermally conductive conduit 540 that is thermally coupled to heatsink 530. For example, in one embodiment, water is used as the liquid. Optionally water may be provided by attaching a source of cold water, such as tap water; referring to FIG. 1, water may be provided through a handle 190 having suitable plumbing. Alternatively, a closed-circuit cooling loop having a heat exchanger (not shown) to remove heat from the liquid; the heat exchanger may be located in handle 190 or base unit 120.

Referring again to FIG. 5, conduit 540 covers at least a portion of one or more surfaces, for example, surface 542 of heat sink 530. A single planar conduit may cover the entirety of one or more surfaces of heat sink 530. Alternatively, a plurality of conduits, each covering a portion of a surface of heat sink 530, may be used. Alternatively, one or more conduits 540 may cover at least a portion of electrodes 515, 516. Since cooling may be applied to either heat sink 530, directly to electrodes 515, 516, a surface of a heatsink (e.g., surface 542), a surface of an electrode, or any other appropriate surface from which heat is to be removed shall hereinafter be referred to as a "cooling surface." While a cooling surface is illustrated as an external surface, it is to be understood that a cooling surface may be an internal surface, such as a surface exposed to a conduit through a heat sink or an electrode.

FIG. 6A is a cross-sectional side view of one example of one embodiment of a cooling system 600 that uses evaporative cooling. In FIG. 6, a phase change liquid is sprayed from one or more spray jets 610 and 620 onto the cooling surface 623. The liquid can be any suitable evaporative liquid such that the liquid evaporates in response to heat absorbed from the cooling surface. In some embodiments, the liquid is a low-temperature boiling point liquid, directed on the heat sink such that as the liquid boils in response to heat absorbed from the cooling surface 623. In some embodiments, the liquid is tetrafluoroethane (boiling point -26°C), CO₂ (boiling point -78°C) although any other suitable liquids (e.g., freon or liquid nitrogen) could also be used. In some embodiments, the liquid is atomized by spray jets 610 and 620.

-18-

Optionally, the liquid can be contained in a container 625 located in the base unit or handle. Preferably, container 625 is conveniently accessible by a user so as to be user-replaceable. A conduit 626 is used to transport the liquid to spray jets 610 and 620. The amount of coolant flow is regulated by valve 627, which can be controlled manually or electrically using information regarding the amount of heat present in a system (e.g., system 500 of FIG. 5). For example, a sensor (e.g., sensor 524 in FIG. 5) can be used to control a feedback-controlled solenoid in valve 627. Optionally, each spray jet 610 and 620 can be a combination valve and spray jet eliminating the need for a separate valve 627.

Optionally, the cooling surface 623 from which evaporation occurs can be textured to increase the surface area from which the liquid can be evaporated. Although triangular texturing 615 of the evaporative surface is shown, any shape suitable for increasing surface area may be implemented. The illustrated triangular texturing 615 may be a part of a linear grooves pattern, a cross-sectional view of a concentric circular groove pattern or any other appropriate groove pattern. Other texturing includes a plurality of projections (e.g., semispheres, cylinders, or pyramids projecting from the cooling surface). Optionally, a collar 630 may be used to surround spray jets 610, 620 and heat sink 530 to contain the spray.

A phase change liquid may also be used to cool the electronic device 644 used to power and/or control a photocosmetic device. In particular, power field effect transistors (FETs) used to control the power of a photocosmetic device generate a large amount of heat. Conventionally, power FETs have been cooled using a relatively large heat sink, and a fan to remove heat. Such systems tend to be large and heavy. Cooling systems according to the present invention provide an alternative method of cooling.

Optionally, a portion of the phase change liquid conduit 626 that provides liquid to remove heat generated by the EMR source may be configured to direct a portion of the phase change liquid to the spray jet 640. Spray jet 640 directs a portion of the phase change liquid onto a cooling surface (e.g., a surface of a heat sink 642). A heat sensor 646 (e.g., a thermistor) may be used to control the amount of liquid projected onto cooling surface, for example, by controlling a valve 650.

FIG. 6B is a schematic of another embodiment of a cooling system 650 for use in a head utilizing a flowing, cooling liquid 605. In FIG. 6B, a high-pressure liquid is maintained in a container 655 (e.g., tetrafluoroethane under 1 to 5 atmospheres of pressure) and projected through a nozzle 660 onto a cooling surface 665. The projected liquid 607 from nozzle 660 may be in the form of droplets or stream of liquid. In some embodiments, the liquid is

- 19 -

projected as a stream to overcome the poor aerodynamic properties (i.e., high drag) of droplets, thus improving the heat removal properties of cooling system 650. As described above, cooling surface 665 may be any material that is a good conductor of heat (e.g., copper or silver). Preferably, cooling surface 665 is selected to have dimensions large enough such that the liquid 655 evaporates from surface 665 rather than drips off said surface.

Projected liquid 607 from nozzle 660 is projected onto cooling surface 665 to form a flowing liquid 60 on cooling surface 665. Nozzle 660 and cooling surface 665 may be selected such that the liquid 607 projected from the nozzle 660 is a stream of liquid the entire distance between the nozzle 660, and upon impinging surface 665 *forms* a flowing liquid at cooling surface 665. Alternatively, nozzle 660 and cooling surface 665 may be selected such that the liquid 607 projected from nozzle 660 may form a spray of droplets between nozzle 660 and cooling surface 665 before aggregating to form a flowing liquid at cooling surface 665. Because liquid projected from nozzle 660 is under high pressure, the flowing liquid on the cooling surface 665 flows across the cooling surface 665 at a relatively high speed V.

Forming a flowing liquid 605 on cooling surface 665 may be used to provide increased heat removal from surface 665 compared to conventional cooling system in which droplets (i.e., a non-flowing liquid) are formed on cooling surface 665. For example, the improved heat removal may result from the fact that droplets (as formed in a conventional system) are not formed in sufficient number or density to achieve and maintain a selected amount of heat removal.

FIG. 6C is a schematic of another embodiment of a cooling system 670 for use in a head, utilizing a cooling liquid 655 and having a cooling chamber 684. Head 670 has sidewalls 675 and a cover 680 having a port 682 for entry of the liquid 655 from nozzle 660. Sidewall 675 and cover 680 form chamber 684. Port 682 may also serve as an exhaust vent for evaporated cooling liquid. As indicated by arrows 686, sidewalls 675 and cover 680 redirect the liquid 655 from cover 680 back to the cooling surfaces 665. The sidewalls 675 are preferably selected to be thermally coupled to the cooling surface 665 such that liquid contacting the sidewalls 675 may remove heat from the cooling surface 665. Optionally, the sidewalls 675 may be integrated with cooling surface 665 such that liquid contacting the sidewall 675 may remove heat. In some embodiments it may be preferable that cover 680 have poor thermal conductivity and poor wetting characteristics for the cooling liquid to improve the likelihood that the cooling liquid will reach the cooling surface 665. For example, in some embodiments, cover 680 is made of a polymer or organic glass. Although chamber

-20-

684 is illustrated as having sidewalls and a cover forming an angle therebetween, the chamber may be formed having a continuous curvature.

Because port 682 operates as an exhaust vent from evaporates liquid 655, the area S of port 682 determines the pressure maintained within chamber 684. In some embodiments, port 682 is selected to have a area S large enough to prevent back pressure that slows the speed of the liquid projected on the cooling surface 665; however, port 682 may be selected to be small enough to allow the cover 680 to redirect a significant portion of liquid back to the cooling surface 665, and to maintain pressure in chamber 684 to keep the liquid from evaporating too quickly. For example, port area S may be approximately one hundred to two hundred times as large as the areas of nozzle 660. In some embodiments, the cooling liquid is selected to be a liquid that has an boiling temperature (i.e., evaporation temperature) of less than -26 degrees Celsius for pressures less than or equal to atmospheric pressure.

FIG. 6D is a cross-sectional side view of an embodiment a luerhead 690 utilizing a cooling liquid in which the exhaust vent 692 is separated from the port 694 through which cooling liquid enters chamber 696. Chamber 696 is bounded by a cooling surface 688, side walls 693, and a cover 695. Cooling surface 688 is thermally coupled to source 525, and optical system 520 via coupling plates (described in greater detail below). A cooling liquid from nozzle 698 is projected onto textured cooling surface 688. A portion of the cooling liquid which does not contact cooling surface 688 directly is redirected by side walls 693, and cover 695 as indicated by arrows 686.

Optionally, cover 695 may be selected to have a resonant frequency to enhance its ability to redirect the liquid to cooling surface 688. Also, optionally a means to reduce the kinetic energy of the liquid (e.g., propeller, not shown) may be placed between the nozzle 698 and the cooling surface 688 to cool the liquid.

FIG. 7 is a cross-sectional side view of an embodiment of a head 700 for contacting skin surface 110. Head 700 has channels 730 and 731 in the electrodes 515, 516. Evaporative cooling may occur along the bottom surface of electrodes 515, 516 and along the surface of channels 730, 731, thus increasing the cooling surface area of head 700. Preferably, the location of channels 730 and 731 is proximate diode laser bar 510. In one embodiment, channels 730, 731 are located along the length of the diode laser bar 510 (i.e., along direction-x). In some embodiments, channels 730, 731 are located proximate a spray jet 610 to receive spray. Channels 730 and 731 may have a rectangular cross section or any other shape appropriate to improve cooling. For example, openings 740, 742 may be flared to receive spray

-21 -

from spray jet 61 . As an alternative to a single channel extending along the length of the diode bar 510, a series of channels may be placed on one or both sides of diode laser bar 510 along the length of the diode laser bar.

FIG. 8 is a cross-sectional side view of another embodiment of a cooling system 800. In FIG. 8, a liquid is used to remove heat from cooling surface 823 but the liquid is not used in spray form. In the illustrated exemplary embodiment, liquid flows out of reservoir 825 into a plurality of channels 832 located within cooling surface 823. The length of each of the plurality of channels 832 extends in the direction of the length of source 510. The liquid is brought into the thermal contact or physical contact with cooling surface 823.

Optional the liquid may be a low-boiling point liquid that evaporates in response to heat absorbed from cooling surface 823. A valve 833 may be used to control the liquid evaporation; when significant cooling is desired, valve 833 is opened and a pressure less than equilibrium is applied to the liquid to facilitate evaporation. The pressure drop causes the liquid to boil, which removes heat from cooling surface 823. Although channels 832 are illustrated as extending in a direction parallel to the length of light source 510, and the channels are illustrated as having rectangular cross sections, other shape of channels 832 aligned in one or more in various directions are possible and are within the scope of the present aspect of the invention. A feedback signal can be derived from a thermal sensor (e.g., sensor 524 in FIG. 5) to control a solenoid in control valve 833.

FIG. 9 is a cross-sectional side view of another exemplary embodiment of a head 900 for contacting a surface 110. Head 900 has a cooling system having a cooling surface 923 that is brought into physical contact with a solid mass (also referred to as a phase change solid). At least a portion of the solid mass 834 changes phase in response to heat absorbed from cooling surface 923. The phase change may be from a solid to liquid, or a solid to a gas. In some embodiments, the solid has a melting temperature between approximately -100C and +30C; however, in some applications, materials undergoing a phase change outside this range, particularly below the range, may be utilized.

In some embodiments, the solid mass is conveniently located within a device handpiece (e.g. handpiece 17 in FIG. 1) so as to be user replaceable. In some embodiments, the solid mass is contained within an insulating sleeve to avoid contact with user's hands, and/or to minimize melting due to exposure to room temperature. In the illustrated embodiment, temperature control can be achieved by using a manually or electrically controlled solenoid or a spring 835 to bring the solid mass in and out of contact with cooling surface 923.

-22-

one embodiment of the phase-change cooling system, the phase-change solid is ice. In this embodiment, a user could keep one or more frozen ice blocks in his/her freezer. When the user wanted to operate the photocosmetic device, a frozen ice block could be inserted in the device. In another embodiment, dry ice, which has a significantly lower melting point than water, could also be used to achieve greater cooling capacity. It is to be understood that the ice block may contain water, or water with one or more additives to treat a user's skin.

- In some embodiments, commercially available organic compounds (e.g., paraffin wax-based materials, fatty acids, cross-linked polyethylenes) may be used as phase change solids. Examples of appropriate paraffin wax materials include RT2 produced by Rubitherm GmbH. RT25.. has a melting point of 27.7°C. In other embodiments, greases having melting points in the 20-3.5°C range may be used as the phase change solid. In another embodiment, Gallium or a Gallium alloy (e.g., Ga/In, Ga/In/Sn, or Ga/In/Sn/Zn), which is tailored to exhibit a melting point in the 15-50°C range, is used as the solid mass. In a Gallium alloy, the relatively high thermal conductivity of Gallium (40.6 W/m*K) and Indium (81.6 W/m*K) would help to spread the waste heat throughout the alloy volume. A disposable phase-change cooler cartridge may be used to contain the phase-change solid; for example, the phase change solid may be used either once and then discarded or may be rechargeable (i.e., resolidified one or more times).

- FIG. 10 is an embodiment of a cooling system in which an endothermic chemical reaction is used for cooling. Examples of appropriate reactions are ammonium nitrate (NH_4NO_3) or ammonium chloride (NH_4Cl) introduced into water causing an endothermic reaction. For example, if 200 ml of water is mixed with 200 g of ammonium nitrate, a temperature of approximately -5°C can be achieved, thus allowing absorption of a heat.

- In FIG. 10, an endothermic reaction is contained within a reaction chamber 1050, and on chamber 1050, and the reaction chamber is thermally coupled to cooling surface 1023. In some embodiments, reaction chamber 1050 could be coupled to the cooling surface 1023 by a material having a good thermal conductivity. In some embodiments, the mechanism includes a thin membrane 1051 separating a first chamber of water and another chamber of potassium chloride. In some embodiments, membrane 1051 can be broken to initiate the reaction and the reaction chamber could be a disposable container. For example, the user could apply force to a flexible plastic reaction chamber to break a membrane and thereby produce a reservoir of cold liquid prior to turning on the device. Alternatively, the membrane may be removed or otherwise manipulated.

- 23 -

according to any **L**own means to allow contents of the first chamber and the second chamber to interact.

FIG. 11 is a cross-sectional side view of an embodiment of a device 1100 having a conduit 1110 and an exhaust vent 1120. In FIG. 11, a liquid or gas entering exhaust vent 1120 is directed to an area of skin 1130 so as to pre or post cool the area of skin 1130 during treatment. For example, a portion of the same cooling liquid that is sprayed onto cooling surface 530 or the gas resulting from the evaporation of the liquid may enter conduit 1110 and be sprayed onto skin by vent 1120. The portion of liquid may be condensed evaporate or simply excess liquid. If, as described above, tap water was utilized for cooling (or an ice phase-change cooler as described with reference to FIG. 9), it may be possible to divert a portion of the water after the water was used to cool the cooling surface 530. In some embodiments, the pressure from a gas resulting from a phase change cooling system may be used to drive a lotion onto a patient's skin. Although the illustrated embodiment illustrates diverting a portion of the cooling liquid after it is used to cool surface 530, in some embodiments a portion of the cooling liquid may be directly projected onto the skin without being used to cool the cooling surface 530.

Optionally, one or more additives may be added to the liquid via conduit 1112 (e.g., to form a cooling lotion) prior to spraying on the skin. The additives could be stored in a cartridge (not shown) in the handpiece or base unit. In some embodiments, to achieve a "shower effect," of the water exiting the heatsink could be exhausted onto the skin. As an alternative to using the evaporative liquid, an alternative source of gas, liquid or lotion (i.e., independent of the cooling system) could be stored in a cartridge in the handpiece or the base unit and dispense while the handpiece is moved across the skin surface.

To avoid confusion, the following exemplary embodiments of optical systems for use with aspects of the present invention will be described with reference to a single electromagnetic radiation source; however as described above, one or more sources may be used to form one or more areas of radiation. In the exemplary optical systems described below, each of the surfaces having optical power has optical power along a first axis (e.g., the y-axis) and zero optical power along an axis normal to the first axis (i.e., the x-axis). That is, the lenses are cylindrical. Although the embodiments discussed below have planar or cylindrical curvatures, other refractive or diffractive optical designs are within the scope of the present invention.

-24-

Fig. 12A is a side view of one example of an embodiment of a single element optical system 1200 appropriate for use with photocosmetic devices according to some aspects of the present invention. Optical system 1200 includes an element 1210 for transmitting light from an electromagnetic radiation source 1220 (e.g., a laser diode bar) to a patient's skin 110.

- 5 Element 1210 has an input surface 1211 and an output surface 1212 configured to contact a patient's skin surface.

- Source 1220 is closely coupled to input surface 1211 of the element 1210 (e.g., 1 mm separation); close coupling enables a large fraction of light along a highly divergent fast-axis of a laser diode source to be transmitted to a patient's skin. In some embodiments, input surface 1211 has an antireflective (AR) coating.

- As described above, element 1210 is made of a material substantially transparent at the operative wavelength, and preferably made of a material that is thermally conductive to remove heat from a treated skin surface (e.g., sapphire). In some embodiments, the lateral sides 1213 of element 1210 are coated with a material reflective at the operative wavelength (e.g., copper, silver or gold). Additionally, the space 1221, between source 1220 and input surface 1211, may be surrounded with a reflective material to increase the strength of light incident on surface 1211.

- In one embodiment, optical element 1210 is a sapphire plate (i.e., surfaces 1211 and 1212 are planar, and have no optical power). In another embodiment of optical system 1200, optical surface 1212 has a cylindrical curvature (as shown in Fig. 12) and is selected to converge light incident on surface 1212. For example, in one embodiment, surface 1212 has a radius of curvature of approximately 3mm. This system can be used to treat skin structures that require high treatment fluence. For example, the lens system of FIG. 1 can be used to target stem cells of hair follicle, sebaceous gland, infratympanic, vascular tissue, tattoos, or collagen.

- In some embodiments, lateral surfaces 1213 have a length L approximately in the range 5- 50 mm, and a cross-sectional width (measured in the x-direction) and height (measured in the y-direction) are selected to collect light from source 1220. For example, for a source comprised of two 1 cm diode laser bars close-coupled to element 1210, the cross-sectional width is selected to be 2 cm, and the cross-sectional height is 2 cm.

As illustrated, optical element 1210 transmits a portion of light from source 1220 directly to surface 1212 with no reflections on lateral surfaces 1213 (e.g., exemplary ray 1230) and a portion of light from source 1220 is reflected from lateral surface 1213 prior to reaching

-25-

surface 1212 (e.g., exemplary ray 1232). An element, such as element 1210, that directs a portion of light from source to surface using total internal reflection is also referred herein to as a "waveguide."

Optionally, a tip reflector 1222 may be added to redirect light scattered out of the skin back into the skin (referred to as photon recycling). For wavelengths in the near-IR, between 40% and 80% of light incident on the skin surface is scattered out of the skin; as one of ordinary skill would understand the amount of scattering is partially dependant on skin pigmentation. By redirecting light scattered out of the skin back toward the skin using tip reflector 1222, the effective fluence provided by system 1200 can be increased by more than a factor of two. In one embodiment, tip reflectors 1222 extend a total of 3 mm from the upper lateral surface and lower lateral surface of element 1210. In some embodiments, tip reflectors 1222 have a Copper, gold or silver coating to reflect light back toward the skin.

A reflective coating may be applied to any non-transmissive surfaces of the device that are exposed to the reflected/scattered light from the skin. As one of ordinary skill in the art would understand, the location and efficacy of these surfaces is dependent on the chosen focusing geometry and placement of the light source(s). Photon recycling is discussed further in U.S. Application 09/634,981, filed August 9, 2000, entitled "Heads for Dermatology Treatment," by A. Tshuler, et al., and application serial number 09/268,433, filed March 12, 1999; the substance of both is hereby incorporated by reference. FIG. 12B is a ray trace of one example of an embodiment of such an optical system 1200 having a source 1220 and an element 1210 as illustrated in FIG. 12A.

FIG. 13 is a side view of one example of an embodiment of a two-element cylindrical optical system 1300 appropriate for use with photocosmetic devices according to some aspects of the present invention, in which a collimator 1310 is used in conjunction with element 1210. In FIG. 13, a fast axis collimator 1310 is very closely coupled to optical source 1220 (e.g., 0.09 mm). In one embodiment, collimator 1310 has a length 1.5 mm, a planar input surface 1311, and an output surface 1312 having a curvature of to collimate the output of collimator 1310. Element 1210 is located 0.1mm from output surface 1312. Collimator 1310 produces a beam of radiation that is substantially collimated in the y-dimension at output surface 1312. For example, collimator 1310 may be a lens module number S-TIH53 produced by Limo GmbH of Doitmund, Germany.

The collimated beam is projected onto input surface 1211 of optical element 1210. As described above, element 1210 may be a plate or may be weakly converging (e.g., output

surface 1212 may have a radius of curvature equal to 3 mm) to compensate for scattering in the skin. This system can be used to treat skin structures that require high treatment fluence. For example, the lens system of FIG. 13 can be used to target stem cells or hair follicle, sebaceous gland, infrapfundulum, vascular, tattoo, or collagen. FIG. 13B is a ray trace of one example of an embodiment of such an optical system 1300 having a source 1200 and a collimator 1310 and an element 1210 as illustrated in FIG. 13A.

FIG. 14A is a side view of another example of an embodiment of a two-element cylindrical optical system 1400 appropriate for use with photocosmetic devices according to some aspects of the present invention. In optical system 1400, the fast-axis collimator 1310 of FIG. 13 is used in conjunction with an element 1420 located 0.1 mm from surface 1312 of collimator 1310 to project light from source 1220. Element 1420 has an input surface 1421 with a curvature of 1 mm, a planar output surface 1422, and a length of 1 mm. System 1400 focuses light at approximately 1 mm from surface 1422 (i.e., 1 mm below the skin surface for embodiments in which surface 1422 is configured to be in contact with a patient's skin). In one embodiment, the heights of elements 1310 and 1420 are selected to be 1.5 mm. In some embodiments, lens 1420 is made of sapphire. This system can be used to target shallow skin structures that require high treatment fluence. For example, the lens system of FIG. 14 can be used to target psoriasis, sebaceous glands, hair shafts, or hair stem cells. FIG. 14B is a ray trace of one example of an embodiment of such an optical system 1400 having a source 1220 and a collimator 1310 and an element 1420 as illustrated in FIG. 14A.

FIG. 15A is a side view of another example of an embodiment of a two-element cylindrical optical system 1500 appropriate for use with photocosmetic devices according to some aspects of the present invention. FIG. 15 illustrates an optical system 1500 that can be used, for example, to focus the diode light deeper than the optical system 1400 in Fig. 14. For example, optical system 1500 may focus the diode light approximately 2 mm below the skin surface (i.e., 2 mm from surface 1522) to target deep structures (e.g. hair bulb, deeper blood vessels, subcutaneous fat) in the skin.

System 1500 is a two-element symmetrical lens system to project light from a source 1220. A first element 1510 is located approximately 1.4 mm from source 1220 and has an input surface 1511 that is planar and an output surface 1512 having a curvature of 2.5 mm; accordingly, lens 1510 quasi-collimates the light from light source 1220. A second lens 1520 having an input surface 1521 with a curvature of 2.5 mm and a planar output surface 1522; accordingly lens 1522 focuses the quasi-collimated light 2 mm below the skin surface. In the

-27-

illustrated embodiment, aberrations in the optical system are balanced to achieve a substantially uniform (i.e., "flat top") spatial optical intensity profile at output surface 1522. The flat top intensity profile is substantially determined by spherical aberration in a plane transverse to the cylindrical surface 1522. In some embodiments, lenses 1510 and 1520 are made of sapphire. FIG. 15B is a ray trace of one example of an embodiment of such an optical system 1500 having a source 1220 and an element 1510 and an element 1520 as illustrated in FIG. 15A.

FIG. 16A is a schematic illustration of an exemplary embodiment of a head 1600 for performing photocosmetic procedures. Head 1600 is illustrated without a housing to facilitate description. As described above head 1600 will be moved along an area of a patient's skin, typically in direction 1602 or direction 1604.

Head 1600 includes an optical system 206 to transmit light from an EMR source 1630. Electrodes 1620 activate an EMR source 1630. An electric insulator 1650 may be located between electrodes 1620 to prevent electrical contact between electrodes 1620. Electrodes 1620 may be taped to reduce the region of contact with a patient's skin.

FIG. 16B is a schematic illustration of an exemplary embodiment of a head 1650 for performing photocosmetic procedures that also provides the capability to perform muscle stimulation during a photocosmetic procedure. Electrical muscle stimulation is a well-known physical therapy procedure that may enhance the efficacy of some photocosmetic procedures. For example, electrical muscle stimulation may be used to improve the efficacy of wrinkle treatment or cell site treatment.

In one embodiment, two electrodes 1610 for delivering the electrical stimulation are located on opposite sides of optical system 206, on a portion of head 1600 that is designed to be in contact with a patient's skin during a photocosmetic treatment (i.e., during the delivery of EMR by system 216). One electrode 1610 contacts an area of a patient's skin prior to optical system 206 and the other electrode 1610 contacts an area of skin after optical system 206.

A thermally conductive electric insulator 1615 (e.g., made of BeO or diamond or other suitable material) can be used to prevent electrical contact between electrodes 1610 which provide electrical stimulation, and electrodes 1620 which activate EMR source 1630. An electric insulator 1650 may be located between electrodes 1620 to prevent electrical contact between electrode 1620.

By applying a constant (or pulsed) electrical current to a patient's skin via electrodes 1610 while the handpiece is scanned across the skin surface, simultaneous muscle stimulation

-28-

and electromagnetic treatment can be achieved. In some embodiments, electrodes may provide radio frequency (RF) current through skin. Alternatively, electrodes, 1610 may provide a DC current or a microwave field. In some embodiments, skin can be selected with a RF current or microwave field to selectively heat a portion of skin to be treated with EMR radiation. Preheating skin may enable the power of the EMR source 1630 to be decreased.

FIG. 17A is a schematic of one example of one embodiment of an apparatus according to some aspects of the invention, which determines contact between an optical element 1704 (e.g., element 1210 of FIG. 12) and the surface of a patient's skin 1701. To provide eye safety, in some embodiments of photocosmetic devices, a contact sensor is used to enable an electromagnetic treatment source (e.g., source 510 of FIG. 5) to activate only when the device is in contact with a patient's skin.

In FIG. 17A, an illumination source 1702 (e.g., diode laser or LED, separate from the treatment source) is mounted a few millimeters (e.g., 5 mm) away from element 1704, and directed toward skin surface 1701. Optionally, illumination source 1702 may be mounted to direct light toward skin surface 1701 through element 1704. Source 1702 may emit radiation at the same wavelength as the treatment source 510 but preferably emit radiation at a different wavelength than the treatment source 510. A detector 1712 is located to detect light from the illumination source that is reflected or scattered from the surface of skin 1701. Optionally, a filter 1708 may be added to selectively transmit light from source 1702, and to eliminate wavelengths of light corresponding to the treatment source 510 and other extraneous wavelengths of light.

In the case of poor or no skin contact, a relatively large amount of radiation light from source 1702 would reflect or scatter from the skin surface 1701 through the optical system 1704 to detector 1712. As illustrated in FIG. 17B, when element 1740 is in good contact with the skin surface 1701, scattering and absorption in the skin would attenuate light from the illumination source 1702, and a relatively small amount of radiation would reach detector 1712. Thus, by using an electronic means (e.g., a comparator) to measure the output of detector 1712, and selecting an appropriate threshold, the treatment source can be configured to activate only when the output of detector 1712 is below the threshold. Optionally, source 1702 and/or detector 1712 may be located in a base unit and one or more optical fibers may be used to couple light from the handpiece to the source or detector.

In another embodiment, detector 1712 detects light from the treatment source to determine contact between element 1740 and skin surface 1701. In such a system, light from

-29-

source 510 is scattered and reflected by skin surface 1701 through element 1704 to detector 1712. A radiation filter 1708 may selectively transmit this scattered and reflected radiation to detector 1712. In this embodiment, the treatment source 510 is maintained at a low-power eye-safe mode until firm contact with the skin surface 1701 is made. When there is no or poor contact between skin surface 1701 and element 1704, the output of detector 1712 is relatively low. However, when element 1704 is in good contact with the skin surface 1701, the output of detector 1701 is relatively high. Thus, treatment source 510 would be configured to fire only when the output of detector 1712 was above a threshold level.

Alternatively, instead of source 1702 and detector 1712, a standard optical contact detector that is in an optical computer system mouse can be used, for example, the optical contact system in a CordLess MousemanTM produced by Logitech of Fremont, CA.

As an alternative to the optical methods of determining contact, electrical methods can be used to detect contact between element 1704 and a patient's skin 1701. FIG. 17C is a cross-sectional view of handpiece having two electrical contacts located in a portion of the handpiece such that when element 1704 is in contact with skin 1701, contacts 1720 are also in contact with skin 1701. Contact can be determined by measuring resistance (or capacitance) between the contacts. Treatment source 510 would be activated when resistance (or capacitance) between contacts 1720 was within a selected range (i.e., a range typical for skin). In another embodiment, contacts 1720 may be magnetic sensors to detect contact with skin surface 1701. In another alternative embodiment, contacts may be mechanical sensors to detect contact with skin surface 1701. For example, one or more spring-loaded pins or buttons may be located such that when element 1704 is in contact with the skin the pin or button is depressed. Multiple sensors, pins, buttons, or other mechanical sensors located around the perimeter of element 1704 could be used to help ensure that the entire surface of element 1704 face was in good contact with skin. Alternatively, contacts 1720 can be conventional load cells to determine contact with skin surface 1701. Contacts, sensors, pins, buttons, or other mechanical sensors that allow for the measurement of resistance or capacitance may be preferred to ensure that the contact is with skin and not with another surface, for example, a mirror or countertop.

In another embodiment, one or more temperature sensors are used to determine contact with skin surface 1701. A typical skin surface temperature is in the 30-32°C range; accordingly temperature sensors could be located near a surface of the device which contacts a patient's skin, and contact could be determined to occur when the measured temperatures were

- 30 -

within a selected range (e.g., 23-27°C). Alternatively, contact could be determined to have occurred when the temperature sensors measured a temperature versus time slope indicative of contact. In still another embodiment, where lotion is to be dispensed on the skin (described above with reference to FIG. 11), skin contact could be detected by using a pressure sensor. within spray jet 1120. The pressure sensor would measure the pressure needed to eject the lotion onto the skin. Only when the handpiece was in good contact the skin would relatively high pressure be provided to dispense the lotion.

Contact sensor designs are described in greater detail in U.S. application 09/847,043, by Henry Zenzie, filed April 30, 2001, entitled "Contact Detecting Method and Apparatus for an Optical Radiation Handpiece," the substance of which is hereby incorporated by reference.

A handpiece is preferably scanned across a patient's skin within a specified speed-range. If the handpiece is moved too slowly (typical minimum speed limit would be between 5 and 25 mm/s depending on the application), the light dosage will be too high and undesired thermal damage may result. Correspondingly, if the handpiece is moved too quickly (typically the maximum speed limit would be between 50 and 500 mm/s depending on the application), the light dosage will be too low to achieve treatment efficacy. Thus, only when the handpiece is scanned within this speed range does the handpiece emit electromagnetic radiation for treatment. An exemplary speed range for operation of a photocosmetic hand piece for hair removal / growth delay is 10 - 500 mm/s which corresponds to the speed ranges with which is approximately equal to the speed which a typical razors passes over the skin.

FIG. 1 8A is a cutaway side view of one embodiment of a handpiece 1800 having a motion sensor 1820 for determining handpiece speed. Motion sensor 1820 may be used to prevent injury to skin 1810 by providing feedback control to a treatment source (e.g., source 510 in FIG. 2), such that if the handpiece remains motionless or if the movement across the skin 1810 is too slow, or too fast, the intensity of source may be decreased or increased, respectively, or the source may be turned off. Optionally, the treatment source may be disabled instead of reduced in power. In one embodiment, a wheel 181 is positioned to make physical contact with skin 1810, such that the wheel rotates as handpiece 1800 is moved relative the skin 1810, and handpiece speed can be determined.

Handpiece 1800 may be configured to inform the operator whether the handpiece speed is inside or outside of an acceptable speed range. For example, a tactile indicator (e.g., a vibrator) could be configured to vibrate the handpiece when the handpiece speed is inside or

outside the desired range. Alternatively, a visual indicator 1804 (e.g., an LED) or an audio indicator (e.g., a beeper) may be used to inform the operator that the handpiece speed is inside or outside the desired range. In some embodiments, multiple indicators 1806 (e.g., LEDs having different colors, or different sound indicators) may be used to inform the operator that the handpiece speed is either too high or too low or is within the desired range.

FIG. 18B is a schematic of one example of an embodiment of a motion sensor system having at least one wheel 1821. Preferably a second wheel 1821 is added and located on an opposite side of optical system 206 to ensure that the entire skin contacting surface of the optical system 206 moves at a rate of speed within the acceptable range to provide uniform illumination on a patient's skin.

In one embodiment, each external wheel 1821 is coupled to a corresponding auxiliary internal wheel 1822 having perforations around its perimeter. A source 1830 projects light in the direction of a corresponding detector 1832 so that as a wheel 1821 rotates, the perforations of auxiliary wheel 1822 alternately transmit and block light projected by source 1830; as a result, as handpiece 1800 (visible in FIG. 18A) moves across a patient's skin, detectors 1832 produce a signal having a chain of pulses.

One of ordinary skill would understand that the speed of the handpiece across a patient's skin is proportional to the rate at which the pulses occur. A controller 1834 correlates the pulse rate to the handpiece speed. The above-described perforated auxiliary wheel design is similar to standard computer system mouse design, for example, a mouse wheel in the Bth Wheel Mouse produced by Logitech Corporation of Fremont, CA, which is just one example of an apparatus to measure handpiece speed, many other apparatus are possible and aspects of this aspect of the invention. For example, in an alternative embodiment, a piezoelectric motor is coupled to wheel 1821 to generate a voltage that is proportional to handpiece speed.

FIG. 19 illustrates another optical apparatus 1900 having a motion sensor for determining handpiece speed. In apparatus 1900, a light source 1902 (e.g. an infrared LED) is coupled into the transmitting fiber 1904. A light detector 1910 (e.g., an inexpensive CCD camera or a diode sensor) is coupled to the end of a receiving fiber 1906. In apparatus 1900, the ends of the transmitting fiber 1904 and receiving fiber 1906 are coupled together to form a single fiber end 1909 that is in contact with the skin 1908. A portion of light projected onto skin surface 1908 by transmitting fiber 1904 through fiber end 1908 is reflected or scattered from the skin surface 1908 and received by receiving fiber 1906 through fiber end 1909 and

- 32 -

detected by detector 1910. Because the skin surface 1908 has a semi-eriodic structure (e.g., the distances between similar tissues such as hair follicle, vessels, glands are almost constant structure) detector output is modulated at a rate dependent on the handpiece speed. *One of ordinary skill would understand that handpiece speed can be calculated from the modulated detector output. Optionally, a second transmitting fiber 1905 and receiving fiber 1907 coupled together through fiber end 1911 may be added, so that the first and second transmitting fiber/*

5 detector output. Optionally, a second transmitting fiber 1905 and receiving fiber 1907 coupled together through fiber end 1911 may be added, so that the first and second transmitting fiber/ and transmitting fiber/

receiving fiber pairs are located on opposite sides of optical system 206 to ensure that the entire skin-contacting surface of optical system 206 moves across the skin with in the acceptable range to provide uniform illumination on a patient's skin.

10 In system 1900, each transmitting fibers 1904, 1905 is coupled to a corresponding receiving fiber 1906, 1907; alternatively, a transmitting fiber and corresponding receiving fiber, may contact the skin at distinct, separated points (i.e., the transmitting fiber and corresponding receiving fiber are not coupled at the skin); in such an embodiment, the ends of the fibers contacting the skin maybe separated by any distance at which photons scattered by tissue layers can be reliably detected. In such embodiments, the upper bound on the fiber spacing occurs when the light coupled into receiving fiber is reduced to a point at which the amount of scattered photons generates a signal that is too small to be accurately detected.

15 Although optical apparatus for measuring handpiece speed have been described, it should be understood that other methods of speed measurement are within the scope of this aspect of the invention. For example, electromagnetic apparatuses that measure handpiece speed by recording the time dependence of electrical (capacitance and resistance)/magnetic properties of the skin as the handpiece is moved relative to the skin. Alternatively, spectrum or amplitude of sound emitted while an object is dragged across the skin surface can be measured and the resulting information used to calculate speed because the acoustic spectrum is dependent on speed. Another alternative is to use thermal sensors to measure handpiece speed, by using two sensors separated by a distance along the direction in which the handpiece is moved along the skin (e.g., one before the optical system and one after). In such embodiments, a first sensor monitors the temperature of untreated skin, which is independent of handpiece speed, and a second sensor monitors the post irradiation temperature; the slower the handpiece speed, the higher the fluence delivered to a given area of the skin, which results in a higher skin temperature measured by the second detector. Therefore, the speed can be calculated based on the temperature difference between the two sensors.

- 33 -

An alternative system to measure handpiece speed using thermal characteristics uses a heat source (e.g. the treatment source or another means of heating an area of skin) located a selected distance from a thermal sensor along the direction in which the handpiece is moved along the skin. In such embodiments, the handpiece speed can be determined from the temperature measured by the thermal sensor. For a low handpiece speed, the heat would have sufficient time to propagate through the skin from the heat source to the thermal sensor; however, at high speed the heat would not have time to reach the thermal sensor. Thus, a high skin temperature measured by the thermal sensor would indicate low speed whereas a low skin temperature would indicate high speed.

In an alternative embodiment of a speed sensor, an optical apparatus is used to measure handpiece speed using-Doppler-shift techniques. In such a system, the wavelength of light from a probe laser is projected onto the skin and the speed is determined by shifted frequency of a reflected portion of the light.

In any of the above embodiments, a speed sensor may be used in conjunction with a contact sensor (e.g., a contact sensor as described above with reference to FIGS. 17A-17C). In one embodiment of a handpiece, both contact and speed are determined by the same component. For example, an optical-mouse-type sensor such as is used on a conventional computer optical mouse may be used to determine both contact and speed. In such a system, a CCD (or CMOS) array sensor is used to continuously image the skin surface. By tracking the speed of a particular set of skin features as described above, the handpiece speed can be measured and because the strength of the optical signal received by the array sensor increases upon contact with the skin, contact can be determined by monitoring signal strength. Additionally, an optical sensor such as a CCD or CMOS device may be used to detect and measure skin pigmentation level or skin type based on the light that is reflected back from the skin; a treatment may be varied according to pigmentation level or skin type.

In some embodiments of the present invention, a motion sensor is used in conjunction with a feedback loop or look-up table to control the radiation source output. For example, the emitted laser power can be increased in proportion to the handpiece speed according to a lookup table. In this way, a fixed skin temperature can be maintained at a selected depth (i.e., by maintaining a constant flux at the skin surface) despite the fact that a handpiece is moved at a range of handpiece speeds. The power used to achieve a given skin temperature at a specified depth is described in greater detail in U.S. Pat. Application No. 09/634,981, which was incorporated by reference herein above. Alternatively, the post-treatment skin temperature may

be monitored, and a feedback loop used to, maintain substantially constant fluence at the skin surface by varying the laser output power. Skin temperature can be monitored by using either conventional thermal sensors or a non-contact mid-infrared optical sensor. The above motion sensors are exemplary; motion sensing can be achieved by other means such as sound (e.g., using Doppler information).

Although the above embodiments were discussed with reference to a system monitoring handpiece speed as moved by an operator, the handpiece could be mounted on a translation stage to move the handpiece at controlled, predetermined speed across the skin surface. In such an embodiment, the apparatus would be positioned relative to the patient to treat a selected area of skin, and the translation stage could be moved to a subsequent area as necessary.

FIG. 20 is a schematic of one example of one embodiment of a handpiece 2000 illustrating some aspects of a self-contained photocosmetic device. Handpiece 2000 includes an optical source 2055, a power supply 2047, an optical system 2044, a cooling system 2046, and a speed and/or contact sensor 2048. The device is shown in contact with an area of skin 2043. Optical system 2044 couples light from light source 2055 into the skin treatment area 2043.

Cooling system 2046 can be a *phase-change* cooler or any other appropriate cooling system. In some embodiments cooling system 2046 is in good thermal contact with the heatsink 2045 (or electrodes or other cooling surface, not shown). A power supply 2047 (e.g., battery or capacitor) supplies electrical current to optical source 2055. Contact and/or speed sensor 2048 ensures safe and effective treatment as described herein above. Although a contact and speed sensor is illustrated as a single component, it should be understood the contact and speed sensor may be different components and there may be multiple of each type of sensor as described above. Control electronics 2049 process data from contact/speed sensors 2048 or other sensors (e.g., thermal sensors) and control optical source 2055 and cooling system 2046. Cooling system 2046 may be cooled prior to treatment via a thermal-contact plate 2050. Power source 2047 may be charged via electrical contact 2051. On/off button 2052 controls the electrical power. A housing 2053 may be used to enclose, protect, or mount one or more of the above parts.

Optionally, a hair removal device 2054 may be located to remove hair prior to irradiation by light from optical source 2055 to ensure that substantially no hair extends above the skin surface. For example, hair removal device 2054 may be a blade razor (e.g., a safety

- 35 -

razor, a cartridge razor), an electric razor, a stripping device wherein the hair adheres to a surface and is pulled out as the handpiece is moved across a user's skin (e.g., a device like the EpiladyTM produced by Happy Lady, Inc.), an abrasive device that grinds the hair, or a chemical compound that dissolves the hair. A hair removal device may be made disposable such that the hair removal device is easily replaceable by a user. In the instance of coarse hair, a razor having on or a plurality of blades may be used; however in the instance of fine hair, an abrasive paper may be used. A body location having coarse hair initially may have fine hair after one or more photocosmetic treatments; accordingly, a blade razor may be used for the first few treatments and an abrasive paper may be used for subsequent treatments. In some embodiments, the abrasive paper may be simply moved across the skin with a stroke of the photocosmetic device; and in other embodiments the paper may be vibrated by a vibrating mechanism (e.g., a motor).

FIG. 21 is a schematic of one example of an embodiment of a handpiece docking station 2100 for cocking a handpiece 2000: Docking station 2100 is contained in housing 2155. Power supply 2156 charges battery/capacitor 2047 via electrical contact 2051. Cooling material 2046 is cooled by chiller 2157 (e.g., a Peltier element). For example, chiller 2157 may be used to recharge a cooling system, by condensing a phase change liquid or freezing a phase change solid. Heatsink 2058 dissipates heat produced by chiller 2157. Heatsink 2058 may utilize gas, liquid, or solid (phase change) media for heat removal or may simply be fins that are cooled by exposure to room temperature. Umbilical 2159 contains wires to supply electrical power to the docking station from an electrical outlet and may further include tubing for water cooling of heatsink 2058. A self-contained photocosmetic device, and a handpiece docking station are described in greater detail in U.S. Application No. 60/292827, filed December 28, 2000, by G. Altshuler et al., entitled "Method and Apparatus for EMR Treatment," the substance of which is hereby incorporated by reference.

For some embodiments of a photocosmetic device, it is advantageous to have one or more replaceable components. For example, in some embodiments, where the handpiece will likely be dropped or otherwise abused, it may be advantageous to make one or more optical systems removable from the handpiece. In addition, to achieve a variety of treatments that each require different optical sources or optical systems (e.g., treatment of pigmented lesion removal and treatment to achieve hair removal), interchangeable optical components would permit the user to perform different applications with the same handpiece. Additionally, for

-36-

systems employing light sources or power sources having a limited lifetime, replacement of the light sources at the end of useful life may be desirable.

FIG. 22 is a schematic of one example of one embodiment of a handpiece 2200 having a detachable head 2210. Handpiece 2200 has a handle 2220 coupled to a head 2210. Handle 2220 may be coupled to head 2210 using any known method of fastening. Preferably head 2210 includes optical components (e.g., head 1600 of FIG. 16A) to facilitate the use of replaceable components.

FIG. 23 is a schematic of one example of an embodiment of a modular handpiece 2300 having one or more components suitable for, ease of manufacturability and/or user-replacement. For example, handpiece 2300 facilitates assembly and/or replacement of a head assembly 2310 (including an optical system), a cooling assembly 2320, and a power assembly 2330. Preferably, modular handpiece 2300 is configured such that when assembled, head assembly 2310 contacts a mating power plug of power assembly 2330.

FIG. 24 is a schematic illustrating an optical assembly 2400 including a source 2410 (e.g., two diode-laser-bars). The source 2410 may be incorporated into a user-replaceable disposable cartridge, including electrodes 2412, heat sink 2430, optical system 2420 and coupling plates 2440. Coupling plates 2440 may be used to fasten optical system 2420, source 2410, and heat sink 2430. Preferably the fastening mechanism of source 2410 is configured to automatically align source 2410 to optical system 2420. Also preferably, coupling plates are made of a material having a good thermal conductivity (e.g., copper) to conduct heat from the optical system 2420. To simplify alignment of source 2410 and element 2420, source 2412 may be fixedly mounted to optical system 2420.

In addition to replacing the source 2410 at the end of its useable lifetime, it may also be desirable to facilitate the user-replacement of light sources 2410 for use for different cosmetic treatments without having to purchase multiple handpieces. Furthermore, it may be desirable to facilitate user-replacement of light sources 2410 based on skin type, air type and/or on the location of the area of skin to be treated (e.g., underarm, bikini, leg, face).

FIG. 25 is a schematic of one example of a photocosmetic device 2500 illustrating some aspects of the present invention. Device 2500 has a head 2580 and a handle 2590. Head 2580 has a first optical system 2510 (e.g., optical system 310 in FIG. 3) to form a first area of radiation (e.g., area 311 in FIG. 3), and a second optical system 2515 (e.g., optical system 315 in FIG. 3) to form a second area of radiation (e.g., area 316 in FIG. 3) on a patient's skin. As described above with reference to FIG. 3, radiation to form the first area and the second area

-37-

may be from a single divided source or two sources (sources not shown). Device 2500 also includes a motion sensor system having a wheel 2521 (e.g., corresponding to wheel 1821 of FIG. 18), and a second wheel 2522 (e.g., corresponding to wheel 1822 of FIG. 18) located on an opposite side of optical system 2510 to ensure that the entire skin contacting surface of the optical element 2510 moves at a rate of speed within the acceptable range to provide substantially uniform illumination on a patient's skin.

FIG. 26A is a schematic of one example of a photocosmetic head 2600 illustrating aspects of the present invention directed to a treating curved area of skin (e.g., a jaw, back or arm). Head 2600 includes two pivoting transmission systems 2610 and 2620 for delivering electromagnetic radiation. The components of head 2600 are substantially contained within a housing 2630 and coupled to a base unit (not shown) via cord 2640. Housing 2630 is illustrated as a transparent wire frame to facilitate description. The size of components of head 2600 may be selected according to the body part with which they are to be used, and multiple heads may be connectable to cord 2640 to permit treatment of various body parts.

Alternatively, each head may have a fixed cord such that each cord can be plugged into a base unit and removed

FIG. 26B is a schematic of one embodiment of two transmission systems 2610 and 2620 of a head to treat a curved surface. Transmission systems 2610 and 2620 are illustrated without a housing to illustrate their relative positioning. FIG. 26B illustrates that transmission systems pivot in at least one rotational direction to facilitate maintenance of contact with a curved area of skin. For example, transmission systems 2610 and 2620 may be mounted at an angle relative to one another (e.g., 5 - 30 degrees) and mounted to enable rotation about axis X and X'.

FIG. 27 is a schematic illustrating an embodiment of some aspects of handpiece 2700 according to the present invention. Handpiece 2700 includes a housing 2710 having a handle 2702 and a head 2704. Handpiece 2700 includes a head assembly 2710 (including an optical system), a cooling assembly 2720, and a power assembly 2730.

FIG. 28 is a schematic illustration of one embodiment of a photocosmetic device 2800 according to at least some aspects of the present invention. Device 2800 includes a handpiece 2810, a base unit 2820, a cord 2826 to couple handpiece 2810 to base unit 2820. Handpiece 2810 may be grasped by an operator to move a head 2830 across a patient's skin (not shown). Head 2830 may be any head as described herein above or any other suitable head to achieve a photocosmetic treatment, for example, any of the treatments described below.

-38-

The following is a discussion of examples of treatments that can be achieved using apparatus and methods according to the present invention; however, the treatments discussed are exemplary and are not intended to be limiting. Apparatus and methods according to the present invention are versatile and may be applied to any known or yet-to-be developed treatments.

Exemplary treatment mechanisms include, absorption of light by a chromophore within a tissue responsible for the unwanted cosmetic condition or by a chromophore in proximity to the tissue. Treatment may be achieved by limited heating of the Large tissue below temperature of irreversible damage or may be achieved by heating to cause irreversible damage (e.g., denaturation). Treatment may be achieved by direct stimulation of biological response to heat, or by induction of a cascade of phenomena such that a biological response is indirectly achieved by heat. A treatment may result from a combination of any of the above mechanisms. Optionally, cooling, DC or AC (RF) electrical current, physical vibration or other physical stimulus in addition or other physical action may be applied to a treatment area or adjacent area to increase the efficacy of a treatment. A treatment may result from a single session, or multiple sessions may be used to achieve a desired clinical effect.

A device according to one or more aspects of the invention may operate in a variety of optical ranges. For example, electromagnetic radiation delivered to the skin may have wavelength within the range 380-1900 nm. The power of the light delivered may be in the range 0.001-300 W/cm², and exemplary scan speeds include 0.1-500 cm/sec. The desired radiation characteristics may be achieved by any suitable LEDs, lamps and diode lasers or any other suitable light source presently available or yet-to-be developed.

Radiation-induced hair removal is a cosmetic treatment that could be performed by apparatus and methods according to aspects of the present invention. In the case of hair removal, the principal target for thermal destruction is the hair bulb and preferably the hair matrix, hair papilla or basement membrane of the bulb. For hair removal treatments, melanin, located in the hair shaft and follicle is the targeted chromophore. While the bulb contains melanin and can thus be thermally treated, the basement membrane, which provides the hair growth communication pathway between the papilla within the bulb and the matrix within the hair shaft, contains the highest concentration of melanin and may be selectively targeted.

Wavelengths between 0.6 and 1.2 μm are typically used for hair removal. By proper combination of power, speed, and focusing geometry, different hair related targets (e.g., bulb, matrix, basement membrane, stem cells) can be heated to the denaturation temperature while

- 39 -

the surrounding dermis remains undamaged. Since the targeted hair follicle and the epidermis both contain melanin, a combination of epidermal contact cooling and long pulsewidth can be used to prevent epidermal damage. A more detailed explanation of hair removal is given in co-pending provisional patent application number 60/363, 871, entitled "METHOD AND APPARATUS FOR HAIR GROWTH CONTROL," by Rox Anderson, et al. filed March 12, 2002, which is hereby incorporated herein by reference.

Hair removal is often required over large areas (e.g. back and legs), and the required power is therefore correspondingly large (on the order of 20-500 W) in order to achieve short treatment times. Current generation diode bars are capable of emitting 40-60 W at 800 nm, which makes the device effective for use in some embodiments of photocosmetic device according to the present invention.

Example methods of hair growth management may be achieved by combining low power irradiation of hair follicles with light and physical extraction of hair shaft, and/or complete or non-complete physical extraction of the hair follicle from the body. According to some embodiments, hair removal is achieved by irradiating a portion of the skin containing the hair follicle with a light source emitting at a range of wavelengths absorbed by melanin or other endogenous or exogenous chromophores in the follicle. Physical extraction can be performed by mechanical, electromechanical or other suitable techniques. This treatment can be used for either temporary hair reduction or permanent hair reduction.

A first exemplary embodiment of a method of hair growth management according to the present invention includes first physically removing hair ("depilation") and then irradiating the skin as described above. According to some embodiments, the hair removal can be adjusted to remove mostly hair shafts from hair follicles; alternatively hair removal may be down to keratinized zone. This depilation can be done by electromechanical depilation or waxing.

Phototreatment can be performed, for example, using one of the embodiments of photocosmetic device described above. According to these embodiments, light is absorbed by melanin in hair matrix and as a result of thermal injury hair growth is decelerated or completely arrested.

Optionally, after depilation but before irradiation, a topical lotion can be applied to the skin (e.g., via a handpiece) in a treatment area to fill empty hair follicles corresponding to the removed hair. In some embodiments, the transparent lotion is selected to have a refractive index in a range suitable to provide a waveguide effect to direct the light to a region of the skin

to be irradiated. Preferably *the* index of refraction of the lotion is big than the index of refraction of water (i.e., approximately 1.33 depending on chemical additives of the water). In *some embodiments, the index of refraction of the lotion is higher than* the index of refraction of the dermis (i.e., approximately 1.4). In some embodiments, the index of refraction of the lotion is higher than *the* index of refraction of the inner root sheath (i.e., approximately 1.55). In embodiments where the index of refraction is greater than the index of refraction of the inner root sheath, light incident on the surface of *the* skin can be delivered directly to hair matrix without significant attenuation.

The effective pulse length used to irradiate the skin is given by the beam size divided by the speed of scanning of the irradiation source. For example, a 2 mm beam size moved at a scanning speed of 50-100 mm/s provides an effective pulse length of 2 - 60 ms. For a power density of 250 W/cm² the effective fluence is 5-10 J/cm², which approximately doubles the fluence of the light delivered by a device without the use of a high index lotion.

In some embodiments, the pH of the lotion can be adjusted to decrease the denaturation threshold of matrix cells. In such embodiments, lower power is required to injure the hair matrix and thus provide hair growth management. Optionally, the lotion can be doped by molecules or ions or atoms with significant absorption of light emitted by the source. Due to increased absorption of light in hair follicle due to the lotion, a lower power irradiation source may be used to provide sufficient irradiation to heat the hair matrix.

A second exemplary embodiment of a method of hair growth management according to the present invention includes first irradiating the skin, and then physically removing hair as described above. By first irradiating the skin, attachment of the hair shaft to the follicle or the hair follicle to dermis is weakened. Consequently, mechanical or electrical depilation may be more easily achieved (e.g., by using a soft waxing or electromechanical epilator) and pain may be reduced.

Irradiation can weaken attachment of hair bulb to skin or subcutaneous fat; therefore it is possible to pull out a significantly higher percentage of the hair follicle from the skin compared to the depilation alone. Because the diameter of the hair bulb is close to the diameter of the outer root sheath, pulling out hair with hair bulb can permanently destroy the entire hair follicle including stem cells. Accordingly, by first irradiating and then depilating, new hair growth can be delayed or terminated.

Treatment of cellulite is another example of a cosmetic problem apparatus and methods according to aspects of the present invention. The formation of

-41-

characteristic Cellulite dimples begins with poor blood and lymph circulation, which in turn inhibits the removal of cellular waste products. For example, unremoved dead cells in the intracellular space may leak lipid over time. Connective tissue damage and subsequent nodule formation occurs due to the continuing accumulation of toxins and cellular waste products.

- 5 The following are two exemplary treatments for cellulite, both of which aim to stimulate both blood flow and fibroblast growth. In a first exemplary treatment, localized areas of thermal damage are created using a treatment source emitting in the near-infrared spectral range (e.g., at a wavelength in the range 650 -1850 nm) in combination with an optical system designed to focus 2-10 mm beneath the skin surface. In one embodiment, light having a
- 10 power density of 1 - 100 W/cm² is delivered to the skin surface, and the apparatus is operated at a speed to create a temperature of 45 degrees Celsius at a distance 5 mm below the skin. Cooling may be applied to avoid or reduce damage to the epidermis to reduce wound formation. Further details of achieving a selected temperature at a selected distance below the skin is given in U.S. Patent Application 09/634, 691, filed August 9, 2000, the substance of
- 15 which was incorporated by reference herein above. The treatment may include compression of the tissue, massage of the tissue, or multipasses over the tissue.

- In a second exemplary treatment, a treatment source emitting near-infrared light (e.g., a light emitting diode emitting at a wavelength in the range 700-1300nm) is used to focus the light at a distance 2 - 10 mm beneath the skin surface, to elevate the dermis/subcutaneous fat
- 20 temperature to a point well below the thermal damage threshold (e.g., a temperature in the range 42 - 60 degrees Celsius). According to the second exemplary treatment, heating may increase the rate of lipolysis (i.e., fat breakdown) and cause apoptosis (i.e., programmed cell death) of fat cells. Optionally, a topical lipolytic cream may be used in combination with the second exemplary treatment; the elevated temperature profile in the dermis/subcutaneous fat
- 25 may enhance cream penetration and thus increase its efficacy. Due to very long thermal relaxation time in subcutaneous fat (i.e., longer than 1 minute), multiple scanning treatments of an area can achieve the desired heating of the fat, while maintaining normal skin surface temperature. The above exemplary treatments may be used for fat metabolism activation and fat reduction.

- 30 Acne is another very common skin disorder that can be treated using apparatus and methods according to aspects of the present invention. Acne results when sebum from the sebaceous gland cannot reach the skin surface via the hair follicle, and a bacterial infection

- 42 -

occurs within the hair follicle. Photocosmetic treatment is an alternative to traditional treatments (e.g., topical and oral medications).

The following are exemplary methods of treating acne according to the present invention. In each of the exemplary methods, the actual treated area may be relatively small (assuming treatment of facial acne), thus a low power CW source may be used. A first possible treatment is to selectively damage the sebaceous gland to prevent sebum production. The sebaceous glands are located approximately 1 mm below the skin surface. By creating a focal spot at this depth and using a wavelength selectively absorbed by lipids (e.g., in proximity of 0.92, 1.2, and 1.7 μm), direct thermal destruction becomes possible. For example, to cause thermal denaturation, a temperature of 45 — 65 degrees Celsius may be generated at approximately 1 mm below the skin surface using any of the methods described in U.S. Patent Application 09/634, 691, filed August 9, 2000, the substance of which was incorporated by reference herein above.

Optionally, a linear matrix of focal spots (as described above with reference to FIG. 4) may be used to create islands of damage. Although the exact position of the sebaceous glands may not be known, each treatment with a matrix of focal spots will result in a certain number of sebaceous glands being damaged. Thus, by treating the area multiple times, a significant number of sebaceous glands will be damaged.

An alternative treatment for acne involves heating a sebaceous gland to a point below the thermal denaturation temperature (e.g., to a temperature 45 — 65 degrees Celsius) to achieve a cessation of sebum production and apoptosis (programmed cell death). Such selective treatment may take advantage of the low thermal threshold of cells responsible for sebum production relative to surrounding cells. Another alternative treatment of acne is thermal destruction of the blood supply to the sebaceous glands (e.g., by heating temperature 60 — 95 degrees Celsius).

For the above treatments of acne, the sebaceous gland may be sensitized to near-infrared radiation by using compounds such as indocyanine green (ICG, absorption near 800 nm) or methylene blue (absorption near 630 nm). Alternatively, non-thermal photodynamic therapy agents such as photofrin may be used to sensitize sebaceous glands. In some embodiments, biochemical carriers such as monoclonal antibodies may be used to selectively deliver these sensitization compounds directly to the sebaceous glands.

- 43 -

Although the above procedures were described as treatments for acne, because the treatments involve damage/destruction of the sebaceous glands (and therefore reduction of sebum output), the treatments may also be used to treat excessively oily skin.

Another light-based method of treating acne involves thermally destruction of the bacteria (*P. acne*) responsible for the characteristic inflammation associated with acne. Destruction of the bacteria may be achieved by targeting porphyrins stored in *P. Acnes*. Porphyrines, such as protoporphyrins, coproporphyrins, and Zn-protoporphyrins are synthesized by aerobic bacteria as their metabolic product. Porphyrines absorb light in the visible spectral region from 400-700 nm, with strongest peak of absorption around 415 nm. By providing light in the selected wavelength ranges in sufficient intensity heat resulting from absorption cause death of the bacteria. For example, the desired effect may be achieved using a treatment source emitting at a wavelength in the range 360-700 nm using an optical system designed to focus 0.2—1mm beneath the skin surface and a power density of 0.01-10 W/cm at the skin surface.

Yet another technique for treating acne involves using light to expand the opening of an infected hair follicle to allow unimpeded sebum outflow. In one embodiment of the technique, a lotion that preferentially accumulates in the follicle opening (e.g., lipid consistent lotion with organic non organic dye or absorption particles) is applied to the skin surface. A treatment source wavelength is matched to an absorption band of the lotion. For example, in the case of ICG doped lotion, the source wavelength is 790-810 nm. By using an optical system to generate a temperature of 45-100 degrees Celsius at the infundibulum/ infrainfundibulum, for example, by generating a fluence of at skin surface (e.g., 1-100 W/cm), the follicle opening can be expanded and sebum is allowed to flow out of the hair follicle and remodeling of infrainfundibulum in order to prevent comedo (i.e., blackhead) formation.

Non-ablative wrinkle treatment, which is now used as an alternative to traditional ablative CO₂ laser skin resurfacing, is another cosmetic treatment that could be performed by apparatus and methods according to aspects of the present invention. Non-ablative wrinkle treatment is achieved by simultaneously cooling the epidermis and delivering light to the upper layer of the dermis to thermally stimulate fibroblasts to generate new collagen deposition.

In wrinkle treatment, because the primary chromophore is water, wavelengths ranging from 0.8-2 μ m appropriate wavelengths of treatment radiation. Since only wrinkles on the face are typically of cosmetic concern, the treated area is typically relatively small and the required

coverage rate (cm^2/sec) is correspondingly low, and a relatively lower treatment source may be used. An optical system providing sub-surface focusing in combination with epidermal cooling may be used to achieve the desired result. Precise control of the upper-dermis temperature is important; if the temperature is too high, the induced thermal damage of the epidermis will be excessive, and if the temperature is too low, the amount of new collagen deposition will be minimal. A speed sensor (in the case of a manually scanned handpiece) or a mechanical drive may be used to precisely control the upper-dermis temperature. Alternatively, a non-contact mid-infrared thermal sensor could be used to monitor dermal temperature.

Vascular lesions (e.g. port-wine stains, rosacea, spider veins) present another cosmetic problem that could be treated by apparatus and methods according to aspects of the present invention. For treatment of vascular lesions, the target chromophore is blood in these lesions. Exemplary treatment wavelengths range from 0.4-0.6 μm for superficial vascular lesions and 0.6-1.3 for deep vascular lesions. In the case of treatment of spider veins, the relatively large size and corresponding long thermal relaxation time of the target tissue requires a large deposition of energy over a long time period to achieve thermal destruction and to preserve the epidermis. In addition, aggressive epidermal cooling (particularly for patients with darker skin type IV-VI) can be used to prevent epidermal damage. The use of CW sources is advantageous in the treatment of lesions because, similar to hair removal, part of the targeted structure (vein wall) contains little blood and must be damaged by thermal diffusion.

Pigmented lesions such as age spots can be removed by selectively targeting the cells containing melanin in these structures. These lesions are located using an optical system focusing at a depth of 100-200 μm below the skin surface and can be targeted with wavelengths in the 0.4-1.1 μm range. Since the individual melanin-bearing cells are small with a short thermal relaxation time, a shallow sub-surface focus is helpful to reach the denaturation temperature.

Elimination of *underarm* odor is another problem that could be treated by an apparatus and methods according to aspects of the present invention. In such a treatment, a source having a wavelength selectively absorbed by the eccrine/apocrine glands is used to thermally damage the eccrine/apocrine glands. Optionally, a sensitization compound may be used to enhance damage.

Tattoo removal is another procedure that can be achieved by apparatus and methods according to aspects of the present invention. Conventional devices for tattoo removal include

- 45 -

short pulsed (110- 0 ns) Q-switched ruby, alexandrite, Nd:YAG and frequency-doubled Nd:YAG for cosmetic tattoo removal. Typically, a source wavelength is selected based on the color of the tattoo to be removed (e.g., a green laser is used to remove a red portion of a tattoo). Since the ink particles are actually incorporated into individual cells, one embodiment of a thermal treatment for tattoo removal cause the rupture of the cells, thereby releasing the ink.

Exemplary embodiments of apparatus according to aspects of the present invention for use in tattoo removal use a CW source, and an optical system selected to tightly focus radiation from a treatment source at the depth where the cells containing the ink particles reside (e.g., 150-700 μm) to rupture the ink-containing cells. Alternatively, it may also be possible to heat the cells below their thermal denaturation point and induce apoptosis. In the case of embodiments designed to cause apoptosis, healing may be enhanced by operating the radiation source in a quas continuous mode while the handpiece is continuously scanned across the skin surface to create areas in which cells are damaged and areas of non-irradiated areas in between. In some embodiments, feedback from a speed sensor could be used to control laser emission and create to equally spaced lines of damage independent of handpiece speed. To completely remove the tattoo, multiple treatments would be required.

In some conventional, relatively expensive tattoo-removal apparatus, a Q-switched frequency-doubled Nd:YAG laser emitting at 0.532 μm is combined with an (Nd:YAG) emitting at 1.064 μm , and alexandrite laser emitting at 0.755 μm ; the lasers are selectively operated to target cells containing various tattoo ink colors. Embodiments of modular apparatus according to aspects of the present invention, provide a relatively low-cost alternative to the above system. For example, an embodiment of the present invention may be configured to allow the use of optical sources emitting at distinct wavelengths or wavelength bands or a single source and optical components to modify the wavelength of the light generated by a source. In particular, to achieve a wavelength close to the 0.755 μm wavelength, a 0.08 μm diode laser bar may be used; and a Nd:YAG crystal module could be inserted into the handpiece that would be pumped by the diode laser bar to produce a wavelength close to the 1.064 μm wavelength; and to produce a wavelength close to the 0.532- μm wavelength, a SHG crystal may be used to double the frequency of a laser diode emitting 1.064 μm wavelength radiation. Alternatively, a self-frequency-doubling crystal, such as Nd:YCOB may be used.

Low-intensity therapy (LIT) is another procedure that can be achieved by apparatus and methods according to aspects of the present invention. LIT may be used for treatment of wounds, carpal-tunnel syndrome treatment, or to stimulate hair growth, or to accelerate biochemical reactions. Power densities and wavelengths (630-820 nm) typically used for LITs may be achieved using diode lasers or LED treatment sources. Optionally one or more of the above treatments may be used for veterinary LIT applications.

Elimination of or reduction of the prominence of stretch marks and scars are procedures that may be achieved using apparatus and methods according to aspects of the present invention. Similar to the case of non-ablative skin resurfacing, to achieve the above procedures, it may be possible to stimulate collagen deposition and wound healing by creating a thin thermally damaged layer in the upper dermis.


Removal of warts is another procedure that can be achieved using apparatus and methods according to aspects of the present invention. Wart removal may be achieved using a source producing light in the region of blood absorption (0.5-0.8 μ m). This wavelength is selectively absorbed by hemoglobin, which appears to shut off the wart's blood supply.

Psoriasis is skin disorder that can be treated using apparatus and methods according to aspects of the present invention. Exemplary embodiments of the present invention configured to treat psoriasis emit at wavelengths near 800 nm. Optionally, one or more sensitization agents such as photodynamic drugs or ICG/Methylene blue may be used. Treatment may be applied several times per week, and may be delivered in several different ways including islands (or lines) of treatment. Additional application of apparatus and methods according to aspects of the present invention include facilitation of delivery of topical medications and cosmetic preparations into skin.

Having thus described the inventive concepts and a number of exemplary embodiments, it will be apparent to those skilled in the art that the invention may be implemented in various ways, and that modifications and improvements will readily occur to such persons. Thus, the examples given are not intended to be limiting. The invention is limited only as required by the following claims and equivalents thereto. The invention is limited only as required by the following claims and equivalents thereto. Also, it is to be understood that the use of the terms "including," "comprising," or "having" is meant to encompass the items listed thereafter and equivalents thereof as well as additional items before, after, or in-between the items listed.

-47-

What is claimed is:



CLAIMS

a

1. A photocosmetic device for use on an area of a patient's skin comprising:
a treatment head for use in close proximity to the patient's skin,
5 at least one source of electromagnetic radiation positioned within the treatment head
and configured to project radiation onto the area of skin;
a cooling surface thermally coupled to the at least one source; and
a mechanism to direct a phase change substance onto the cooling surface.
- 10 2. The device of claim 1, wherein the phase change substance comprises a liquid.
3. The device of claim 1, wherein the phase change substance comprises a solid.
4. The device of claim 1, wherein the cooling surface has a texture
- 15 5. The device of claim 4, wherein the texture is a linear groove pattern.
6. The device of claim 4, wherein the texture is a concentric groove pattern.
- 20 7. The device of claim 4, wherein the texture is a plurality of projections.
8. The device of claim 2, wherein the mechanism comprises a spray jet.
9. The device of claim 8, wherein the mechanism further comprises, a valve coupled to
25 the spray jet, wherein the valve controls the amount of liquid projected into the cooling
surface.
10. The device of claim 9 further comprising a heat sensor to produce a signal indicative of
the temperature of at least a portion of the area of skin, and a controller to receive the signal
30 from the heat sensor and control the valve in response to the temperature
11. The device of claim 1 further comprising a container to hold the substance, the
container coupled to the mechanism.

- 49 -

a

12. The device of claim 2, wherein the liquid comprises a refrigerant.
13. The device of claim 12, wherein the refrigerant comprises tetra fluoroethane.
14. The device of claim 3, wherein the solid comprises ice.
15. The device of claim 3, wherein the solid comprises an organic compound.
- 10 16. The device of claim 3, wherein the solid is an Gallium alloy.
17. The device of claim 1, wherein the cooling surface is a surface of a thermally conductive electrode providing power to the source.
- 15 18. The device of claim 1, wherein the cooling surface is a surface of a thermally conductive heat sink that is thermally coupled to the source.
19. The device of claim 2, wherein the at least one source has a length, and the cooling surface has at least one channel therethrough to receive the phase change substance.
- 20 20. The device of claim 2, wherein the at least one source has a length, and the cooling surface has a plurality of channels therethrough to receive the phase change substance, the plurality of channels aligned along the length.
- 25 21. A photodynamic device for use on an area of a patient's skin comprising:
 - a treatment head for use in close proximity to the patient's skin;
 - at least one electromagnetic radiation source located within the treatment head configured to project radiation through the treatment head onto the area of skin; and
 - a first mechanism coupled to the treatment head and configured to project a first
- 30 substance onto the patient's skin.
22. The device of claim 21, further comprising, an optical system to transmit radiation to the area of skin, the optical system having a surface configured to contact the patient's skin.

23. The device of claim 21, further comprising a cooling surface thermally coupled to the at least one source and said surface, and a second mechanism to project a phase change substance onto the cooling surface, wherein the first mechanism is configured to use a gas
5 formed by the phase change of the phase change substance to drive the first substance onto the patient's skin.

24. The device of claim 21, further comprising a cooling surface thermally coupled to the source and said surface, and a second mechanism configured to project a first portion of the
10 first substance onto the cooling surface.

25. The device of claim 24, wherein the first substance is a liquid and a second portion of the first substance projected onto the skin is a gas resulting from a phase change of the first substance.
15

26. The device of claim 24, wherein the first substance is, a solid and a second portion of the first substance projected onto the skin is a liquid resulting from a phase change of the first substance.

20 27. The device of claim 24, wherein the first substance is a solid and a second portion of the first substance projected onto the skin is a gas resulting from a phase change of the first substance.

28. The device of claim 21, wherein the first substance comprises a liquid.
25

29. The device of claim 28, wherein the liquid comprises a lotion.

30. The device of claim 21, wherein the first substance comprises a gas.

30 31. The device of claim 30, wherein the gas comprises cooled air.

32. The device of claim 21, wherein the first substance comprises a plurality of components.

-51-

33. The device of claim 23, wherein the cooling surface is a surface of a thermally conductive electrode providing power to the source.

34. The device of claim 23, wherein the cooling surface is a surface of a thermally conductive heat sink that is thermally coupled to the source.

35. The device of claim 21, wherein the source is one of a diode laser bar, light emitting diode and lamp.

10

36. A device for use on all area of a patient's skin comprising:
a treatment head for use in close proximity to the patient's skin;
at least one electromagnetic radiation source positioned in the treatment head and configured to project electromagnetic radiation onto the area of skin;

15

a cooling surface thermally coupled to the at least one source of electromagnetic radiation and including at least one channel therethrough; and

a mechanism to project a substance onto the cooling surface, and into the at least one channel.

20 37. The device of claim 36, wherein the substance is a liquid.

38. The device of claim 36, wherein the substance is a gas.

39. A device for use on an area of a patient's skin comprising:

25

at least one electromagnetic radiation source configured to project radiation onto the area of skin;

a cooling surface thermally coupled to the at least one source; and

a solid mass thermally coupled to the cooling surface, the solid mass changing phase in response to heat absorbed from the cooling surface.

30

40. The device of claim 39, wherein the solid mass is ice.

41. The device of claim 39, wherein the solid mass is dry ice.

-52-

42.. The device of claim 39 further comprising a mechanism to bring the solid mass into contact with the cooling surface.

5 43. The device of claim 39 further comprising a treatment head, wherein the source is positioned within the treatment head.

44. The device of claim 39, wherein the source is one of a diode laser bar, light emitting diode and lamp.

10

45. The device of claim 39, wherein the cooling surface is a surface of a thermally conductive electrode providing power to the source.

15 46. The device of claim 39, wherein the cooling surface is a surface of a thermally conductive heat sink that is thermally coupled to the source.

47. A device for use on an area of a patient's skin comprising:
at least one electromagnetic radiation source configured to project electromagnetic radiation onto the area of skin;
20 a cooling surface thermally coupled to the at least one source;
a solid mass thermally coupled to the cooling surface, at least a portion of the mass becoming a liquid in response to absorption of heat from the cooling surface; and
an exhaust vent configured to receive a portion of the liquid and to reject the portion of the liquid onto the patient's skin.

25

48. The device of claim 48, further comprising a mechanism for combining the liquid with a chemical substance and directing the liquid and chemical combination onto the patient's skin.

49. A device for use on an area of a patient's skin comprising:
30 at least one electromagnetic radiation source configured to project electromagnetic radiation onto the area of skin;
a cooling surface thermally coupled to the at least one source;

-53-

a reaction chamber thermally coupled to the cooling surface and containing at least a first chemical compound and a second chemical compound, the first and second chemical compounds selected to provide an endothermic reaction within the reaction chamber.

50. The device of claim 49, wherein the cooling surface is a surface of a thermally conductive electrode providing power to the source.

51. The device of claim 49, wherein the cooling surface is a surface of a thermally conductive heat sink that is thermally coupled to the source.

10

52. A device or use on an area of a patient's skin comprising:
 a treatment head for use in close proximity to the patient's skin;
 at least one source of electromagnetic radiation positioned in the treatment head and
 configured to project electromagnetic radiation onto the area of skin; and
 15 a cooling surface thermally coupled to the at least one source of electromagnetic
 radiation, the cooling surface having a channel therethrough to allow a low-boiling point liquid
 to flow onto a surface of the cooling surface.

20

53. The device of claim 52 further comprising a valve connected to the channel to control
 the evaporation of the low-boiling point liquid.

25

54. The device of claim 53 further comprising a heat sensor to produce a signal indicative
 of the temperature of the area of skin, and a controller to receive the signal from the heat
 sensor and control the valve in response to the signal.

55. The device of claim 52 wherein a pressure source is coupled to the channel to control
 the boiling of the low-boiling point liquid.

30

56. The device of claim 52 wherein the source is one of a laser diode bar, light emitting
 diode and lamp.

57. A device or use on an area of a patient's skin comprising:
 a treatment head for use in close proximity to the patient's skin;

al least one electromagnetic radiation source positioned in the treatment head and configured to project radiation onto the area of skin;
a heat spreader thermally coupled to the at least one source; and
a cooling surface thermally coupled to the heat spreader.

5

58. The applicator of claim 57, wherein the source is one of a diode laser bar, light emitting diode and lamp.

59. The device of claim 57, wherein the cooling surface is a surface of a thermally conductive electrode providing power to the source.

10

60. The device of claim 57, wherein the cooling surface is a surface of a thermally conductive heat sink that is thermally coupled to the source.

15 61. A cooling system for cooling a heat generating device:
a cooling surface thermally coupled to the heat generating device;
a nozzle configured to project a high pressure liquid, the liquid forming a flowing liquid on the cooling surface.

20 62. The cooling system of claim 61, wherein the high pressure liquid forms a stream the entire distance between the nozzle and the cooling surface.

63. The cooling system of claim 61, wherein the cooling surface is textured.

25 64. The cooling system of claim 61 further comprising a cooling chamber to redirect the liquid to the cooling surface.

65. The cooling system of claim 64 wherein the cooling chamber includes sidewalls and a cover.

1 / 33




Fig. 1




Fig. 2A




Fig. 2B

3/33




Fig. 3




Fig. 4

4/33

500




Fig. 5

5/33




Fig. 6A




Fig. 6B





Fig. 6C

7133



8/33




Fig. 7




Fig. 8




Fig. 9




Fig. 10

11/33




Fig. 11




Fig. 12A




Fig. 13A

13/33




Fig. 12B

14/33




Fig. 13B

15/33

1400



Fig. 14A

1500




Fig. 15A

16/33




Fig. 14B

17/33




Fig. 15B

18/33

1600




Fig. 16A

19/33




Fig. 16B

20/33




Fig. 17A




Fig. 17B

21/33




Fig. 17C

22/33




Fig. 18A

23/33




Fig. 18B

24/33




Fig. 19

25/33




Fig. 20

26/33




Fig. 21

27/33




Fig. 22

28/33




Fig. 23

29/33




Fig. 24

30/33




Fig. 25

31/33




Fig. 26A




Fig. 26B

32/33




Fig. 27

33/33




Fig. 28

INTERNATIONAL SEARCH REPORT		International application No. PCT/US02/ 16435
A. CLASSIFICATION OF SUBJECT MATTER IPC(7) : A61B 18/18 US CL : 606/9 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 606/9		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) NONE		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,344,413 A (GHAFARI) 06 September 1994, see entire document	1,11,18,36,38,52
X	US 6,059,822 A (BARONOV) 09 May 2000, see entire document	1,2,8-12,18,19,36,38,52-54,61,62,64,65
X	US 5,968,033 A (FULLER et al) 19 October 1999, see entire document	21,22,24,28,34
X	US 5,820,625 A (BAUMGARDNER) 13 October 1998, see entire document	1,2;8-13,18,19,36-38,52-54,61,62
A	US 5,810,801 A (ANDERSON et al) 22 September 1998, see entire document	1-65
Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to disclose the state of the art which is not considered to be prior art for the purposes of the invention	
"E" earlier application or patent published at or after the international filing date	"C" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	
"L" document which may throw doubt on priority "claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family	
"P" document published prior to priority date claimed		
Date of the actual completion of the international search	Date of mailing of the international search report 6 SEP 2002	
29 July 2002 (29.07.2002)		
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20540	Telephone No. 703-308-3520	
Facsimile No. (703)305-3200		